


Victaulic Suction Diffuser Series 731-D



1.0 PRODUCT DESCRIPTION

Available Sizes

- 3 x 2" to 12 x 12"/DN80 x DN50 to DN300 x DN300

Pressure Class

- Rated to the working pressure of the mating flange up to a maximum of 365 psi/2517 kPa/25 bar.

Application

- Provides optimum flow conditions at the inlet side of the pump.
- Removable basket and fine mesh sleeve act as start-up strainer.
- Pressure port in the cap measures pressure downstream of the diffuser.
- Plug in the cap allows for easy draining of the system

2.0 CERTIFICATION/LISTINGS

Not applicable – contact Victaulic with any questions.

ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.

System No.		Location	
Submitted By		Date	

Spec Section		Paragraph	
Approved		Date	

3.0 SPECIFICATIONS – MATERIAL

Housing (Body, Coupling, End Cap): Ductile iron conforming to ASTM A395.

Housing Coating: (specify choice)

Standard: Orange enamel.

Optional: Hot dipped galvanized.

Coupling Gasket: (specify choice)

Victaulic EPDM

(Green color code). Temperature range –30°F to +230°F/–34°C to +110°C. UL Classified in accordance with ANSI/ NSF 61 for cold +73°F/+23°C and hot +180°F/+82°C potable water service and ANSI/NSF 372. NOT RECOMMENDED FOR PETROLEUM SERVICES.

Victaulic Nitrile

(Orange color code). Temperature range +10°F to +150°F/–12°C to +65°C. Not compatible for hot water services over +150°F/+66°C or for hot dry air over +140°F/60°C. NOT RECOMMENDED FOR HOT WATER SERVICES.

Diffuser: Type 304 stainless steel, frame and perforated sheet with 5/32" / 4 mm diameter holes.

Start-Up Pre-Filter: 20 mesh stainless steel, Type 304.


Bolts/Nuts: Heat-treated plated carbon steel, trackhead meeting the physical and chemical requirements of ASTM A449 and physical requirements of ASTM A183.

Support: Boss for support. See table below for size. (Support not supplied.)

4.0 DIMENSIONS

ANSI Dimensions

Series 731-D with ANSI Class 150 Flange




3 - 12⁷/₈₀ - 300 mm

Size		Dimensions							Approx. Weight (Each)
System Side Grooved	Pump Side x Flange ANSI Class 150	L	L1	H1	H2	Thread Size	E		
Nominal Size		inches mm	inches mm	inches mm	inches mm		inches mm	lb kg	
3 80	x	2	11.00	6.30	5.51	3.30	1-11.5 NPT	7.48	20.1
		50	279	160	140	83	190	9.1	
		2.5	11.00	6.30	5.51	3.70	1-11.5 NPT	7.48	26.0
		65	279	160	140	93	190	11.8	
4 100	x	3	11.00	6.30	5.51	4.00	1-11.5 NPT	7.48	27.7
		80	279	160	140	101	190	12.6	
		2.5	13.00	7.40	6.50	3.70	1-11.5 NPT	8.74	29.7
		65	330	187	165	93	222	13.5	
5 125	x	3	13.00	7.40	6.50	4.00	1-11.5 NPT	8.74	31.6
		80	330	187	165	101	222	15.0	
		4	13.00	7.40	6.50	4.60	1-11.5 NPT	8.74	34.6
		100	330	187	165	116	222	15.7	
6 150	x	3	15.00	8.40	7.52	4.00	1.25-11.5 NPT	9.84	46.2
		80	381	213	191	101	250	21.0	
		4	15.00	8.40	7.52	4.60	1.25-11.5 NPT	9.84	49.4
		100	381	213	191	116	250	22.4	
8 200	x	5	15.00	8.40	7.52	5.10	1.25-11.5 NPT	9.84	52.3
		125	381	213	191	130	250	23.7	
		4	16.00	9.00	8.00	4.60	1.25-11.5 NPT	10.98	64.0
		100	406	229	203	116	279	29.0	
10 250	x	5	16.00	9.00	8.00	5.10	1.25-11.5 NPT	10.98	67.3
		125	406	229	203	130	279	30.0	
		6	16.00	9.00	8.00	5.70	1.25-11.5 NPT	10.98	70.3
		150	406	229	203	144	279	31.9	
12 300	x	5	19.00	10.20	9.02	5.10	1.25-11.5 NPT	12.52	98.5
		125	483	260	229	130	318	44.7	
		6	19.00	10.20	9.02	5.70	1.25-11.5 NPT	12.52	102.1
		150	483	260	229	144	318	46.3	
10 250	x	8	19.00	10.20	9.02	6.80	1.25-11.5 NPT	12.52	110.7
		200	483	260	229	172	318	50.2	
		6	23.00	12.40	11.00	5.70	1.25-11.5 NPT	15.55	150.6
		150	584	315	279	144	395	68.3	
12 300	x	8	22.50	12.40	11.00	6.80	1.25-11.5 NPT	15.55	159.9
		200	584	315	279	172	395	72.5	
		10	22.50	12.40	11.00	8.07	1.25-11.5 NPT	15.55	172.0
		250	584	315	279	205	395	78.0	
12 300	x	8	27.00	15.43	13.19	6.75	1.25-11.5 NPT	18.58	245.4
		200	686	392	335	172	472	111.3	
		10	26.84	15.43	13.19	8.07	1.25-11.5 NPT	18.58	260.3
		250	686	392	335	205	472	118.1	
	12	26.84	15.43	13.19	9.50	1.25-11.5 NPT	18.58	273.2	
	300	686	392	335	241	472	123.9		

4.1 DIMENSIONS

DIN Dimensions

Series 731-D with PN10/PN16 Flange




80 – 300 mm

Size		Dimensions							Approx. Weight (Each)
System Side Grooved	Pump Side x Flange ANSI Class 150	L	L1	H1	H2	Thread Size	E		
Nominal Size		mm inches	mm inches	mm inches	mm inches		mm inches	kg lb	
76.1 mm	x 50	2	279 11.00	160 6.30	140 5.50	83 3.30	1-11 ISO 7-1	190 7.50	9.1 20.1
		3	279 11.00	160 6.30	140 5.50	83 3.30	1-11 ISO 7-1	190 7.50	9.1 20.1
80	x 50	2	279 11.00	160 6.30	140 5.50	93 3.70	1-11 ISO 7-1	190 7.50	12.6 27.7
		3	279 11.00	160 6.30	140 5.50	101 4.00	1-11 ISO 7-1	190 7.50	12.6 27.7
100	x 76.1 mm	4	330 13.00	187 7.40	165 6.50	93 3.70	1-11 ISO 7-1	222 8.70	15.0 31.6
		3	330 13.00	187 7.40	165 6.50	101 4.00	1-11 ISO 7-1	222 8.70	15.0 31.6
		4	330 13.00	187 7.40	165 6.50	116 4.60	1-11 ISO 7-1	222 8.70	15.7 34.6
139.7 mm	x 76.1 mm	3	381 15.00	213 8.40	191 7.50	93 3.70	1.25-11 ISO 7-1	250 9.80	16.8 37.0
		4	381 15.00	213 8.40	191 7.50	101 4.00	1.25-11 ISO 7-1	250 9.80	19.1 42.0
		5	381 15.00	213 8.40	191 7.50	116 4.60	1.25-11 ISO 7-1	250 9.80	20.0 44.0
		6	381 15.00	213 8.40	191 7.50	130 5.10	1.25-11 ISO 7-1	250 9.80	22.2 49.0
125	x 80	3	381 15.00	213 8.40	191 7.50	101 4.00	1.25-11 ISO 7-1	250 9.80	21.0 46.2
		4	381 15.00	213 8.40	191 7.50	116 4.60	1.25-11 ISO 7-1	250 9.80	22.4 49.4
		5	381 15.00	213 8.40	191 7.50	130 5.10	1.25-11 ISO 7-1	250 9.80	23.7 52.3
150	x 100	4	406 16.00	229 9.00	203 8.00	116 4.60	1.25-11 ISO 7-1	279 11.00	29.0 64.0
		5	406 16.00	229 9.00	203 8.00	130 5.10	1.25-11 ISO 7-1	279 11.00	30.0 67.3
		6	406 16.00	229 9.00	203 8.00	130 5.10	1.25-11 ISO 7-1	279 11.00	30.0 67.3
		7	406 16.00	229 9.00	203 8.00	144 5.70	1.25-11 ISO 7-1	279 11.00	31.9 70.3
		8	406 16.00	229 9.00	203 8.00	172 6.80	1.25-11 ISO 7-1	279 11.00	31.9 70.3
200	x 139.7 mm	8	483 19.00	260 10.20	229 9.00	130 5.10	1.25-11 ISO 7-1	318 12.50	44.7 98.5
		9	483 19.00	260 10.20	229 9.00	130 5.10	1.25-11 ISO 7-1	318 12.50	44.7 98.5
		10	483 19.00	260 10.20	229 9.00	144 5.70	1.25-11 ISO 7-1	318 12.50	46.3 102.1
		11	483 19.00	260 10.20	229 9.00	172 6.80	1.25-11 ISO 7-1	318 12.50	50.2 110.7
		12	483 19.00	260 10.20	229 9.00	172 6.80	1.25-11 ISO 7-1	318 12.50	50.2 110.7

4.1 DIMENSIONS (Continued)

DIN Dimensions

Series 731-D with PN10/PN16 Flange




80 – 300 mm

Size		Dimensions						Approx. Weight (Each)	
System Side Grooved	Pump Side x Flange ANSI Class 150	L	L1	H1	H2	Thread Size	E		
Nominal Size		mm inches	mm inches	mm inches	mm inches		mm inches	kg lb	
250 10	x	150	584	315	279	144	1.25-11 ISO 7-1	395	68.3
		6	23.00	12.40	11.00	5.70		15.60	150.6
		200	584	315	279	172	1.25-11 ISO 7-1	395	72.5
		8	23.00	12.40	11.00	6.80		15.60	159.9
300 12	x	250	584	315	279	205	1.25-11 ISO 7-1	395	78.0
		10	23.00	12.40	11.00	8.10		15.60	172.0
		200	686	392	335	172	1.25-11 ISO 7-1	472	111.3
		8	27.00	15.40	13.20	6.80		18.60	245.4
	250	686	392	335	205	1.25-11 ISO 7-1	472	118.1	
	10	27.00	15.40	13.20	8.10		18.60	260.3	
		300	686	392	335	241	1.25-11 ISO 7-1	472	123.9
		12	27.00	15.40	13.20	9.50		18.60	273.2

4.2 DIMENSIONS

GB Dimensions

Series 731-D with GB Flange




76.1 – 300 mm

Size		Dimensions							Approx. Weight (Each)
System Side Grooved	Pump Side x Flange ANSI Class 150	L	L1	H1	H2	Thread Size	E		
Nominal Size		mm inches	mm inches	mm inches	mm inches		mm inches	kg lb	
76.1 mm	x 50	279 11.00	160 6.3	140 5.50	83 3.30	1-11 ISO 7-1	190 7.50	9.1	
	2							20.1	
80	x 50	279 11.00	160 6.3	140 5.50	83 3.30	1-11 ISO 7-1	190 7.50	9.1	
		2						20.1	
	76.1 mm	279 11.00	160 6.3	140 5.50	93 3.70	1-11 ISO 7-1	190 7.50	12.6	
		2						27.7	
100	x 80	279 11.00	160 6.3	140 5.50	101 4.00	1-11 ISO 7-1	190 7.50	12.6	
		3						27.7	
	76.1 mm	330 13.00	187 7.4	165 6.50	93 3.70	1-11 ISO 7-1	222 8.70	15.0	
		2						31.6	
139.7 mm	x 80	330 13.00	187 7.4	165 6.50	101 4.00	1-11 ISO 7-1	222 8.70	15.0	
		3						31.6	
	100	330 13.00	187 7.4	165 6.50	116 4.60	1-11 ISO 7-1	222 8.70	15.7	
		4						34.6	
139.7 mm	x 76.1 mm	381 15.00	213 8.4	191 7.50	93 3.70	1.25-11 ISO 7-1	250 9.80	16.8	
		2						37.0	
	80	381 15.00	213 8.4	191 7.50	101 4.00	1.25-11 ISO 7-1	250 9.80	19.1	
		3						42.0	
150	x 100	381 15.00	213 8.4	191 7.50	116 4.60	1.25-11 ISO 7-1	250 9.80	20.0	
		4						44.0	
	139.7 mm	381 15.00	213 8.4	191 7.50	130 5.10	1.25-11 ISO 7-1	250 9.80	22.2	
		2						49.0	
150	x 100	406 16.00	229 9.0	203 8.00	116 4.60	1.25-11 ISO 7-1	279 11.00	29.0	
		4						64.0	
	139.7 mm	406 16.00	229 9.0	203 8.00	130 5.10	1.25-11 ISO 7-1	279 11.00	30.0	
		2						67.3	
200	x 125	406 16.00	229 9.0	203 8.00	130 5.10	1.25-11 ISO 7-1	279 11.00	30.0	
		5						67.3	
	150	406 16.00	229 9.0	203 8.00	144 5.70	1.25-11 ISO 7-1	279 11.00	31.9	
		6						70.3	
200	x 139.7 mm	483 19.00	260 10.2	229 9.00	130 5.10	1.25-11 ISO 7-1	318 12.50	44.7	
		2						98.5	
	125	483 19.00	260 10.2	229 9.00	130 5.10	1.25-11 ISO 7-1	318 12.50	44.7	
		5						98.5	
150	483 19.00	260 10.2	229 9.00	144 5.70	1.25-11 ISO 7-1	318 12.50	46.3		
	6						102.1		
200	483 19.00	260 10.2	229 9.00	172 6.80	1.25-11 ISO 7-1	318 12.50	50.2		
	8						110.7		

4.2 DIMENSIONS (Continued)

GB Dimensions

Series 731-D with GB Flange




76.1 – 300 mm

Size		Dimensions						Approx. Weight (Each)	
System Side Grooved	Pump Side x Flange ANSI Class 150	L	L1	H1	H2	Thread Size	E		
Nominal Size		mm inches	mm inches	mm inches	mm inches		mm inches	kg lb	
250 10	x 6	150	584	315	279	144	1.25-11 ISO 7-1	395	68.3
		200	584	315	279	172		395	150.6
	x 8	250	584	315	279	205	1.25-11 ISO 7-1	395	72.5
300 12	x 8	200	686	392	335	172	1.25-11 ISO 7-1	472	111.3
		250	686	392	335	205		472	245.4
	x 10	300	686	392	335	241	1.25-11 ISO 7-1	472	118.1
		300	686	392	335	241	1.25-11 ISO 7-1	472	260.3
	x 12	300	686	392	335	241	1.25-11 ISO 7-1	472	123.9
		300	686	392	335	241	1.25-11 ISO 7-1	472	273.2

4.3 DIMENSIONS

JIS Dimensions

Series 731-D with JIS 10K Flange




350A – 600A mm

Size		Dimensions						Approx. Weight (Each)
System Side Grooved	Pump Side x Flange ANSI Class 150	L	L1	H1	H2	Thread Size	E	
Nominal Size		mm inches	mm inches	mm inches	mm inches		mm inches	kg lb
76.1 mm	x 50A 2	279 11.00	160 6.30	140 5.50	83 3.30	1-11 ISO 7-1	190 7.50	9.1 20.1
80A 3	x 50A 2	279 11.00	160 6.30	140 5.50	83 3.30	1-11 ISO 7-1	190 7.50	9.1 20.1
	76.1 mm	279 11.00	160 6.30	140 5.50	93 3.70	1-11 ISO 7-1	190 7.50	12.6 27.7
	80A 3	279 11.00	160 6.30	140 5.50	101 4.00	1-11 ISO 7-1	190 7.50	12.6 27.7
100A 4	x 76.1 mm	330 13.00	187 7.40	165 6.50	93 3.70	1-11 ISO 7-1	222 8.70	15.0 31.6
	80A 3	330 13.00	187 7.40	165 6.50	101 4.00	1-11 ISO 7-1	222 8.70	15.0 31.6
	100A 4	330 13.00	187 7.40	165 6.50	116 4.60	1-11 ISO 7-1	222 8.70	15.7 34.6
139.7 mm	x 76.1 mm	381 15.00	213 8.40	191 7.50	93 3.70	1.25-11 ISO 7-1	250 9.80	16.8 37.0
125A 5	x 76.1 mm	381 15.00	213 8.40	191 7.50	93 3.70	1.25-11 ISO 7-1	250 9.80	16.8 37.0
	80A 3	381 15.00	213 8.40	191 7.50	101 4.00	1.25-11 ISO 7-1	250 9.80	21.0 46.2
	100A 4	381 15.00	213 8.40	191 7.50	116 4.60	1.25-11 ISO 7-1	250 9.80	22.2 49.0
	125A 5	381 15.00	213 8.40	191 7.50	130 5.10	1.25-11 ISO 7-1	250 9.80	23.7 52.3
150A 6	x 100A 4	406 16.00	229 9.00	203 8.00	116 4.60	1.25-11 ISO 7-1	279 11.00	29.0 64.0
	139.7 mm	406 16.00	229 9.00	203 8.00	130 5.10	1.25-11 ISO 7-1	279 11.00	30.0 67.3
	125A 5	406 16.00	229 9.00	203 8.00	130 5.10	1.25-11 ISO 7-1	279 11.00	30.0 67.3
	150A 6	406 16.00	229 9.00	203 8.00	144 5.70	1.25-11 ISO 7-1	279 11.00	31.9 70.3
200A 8	x 139.7 mm	483 19.00	260 10.20	229 9.00	130 5.10	1.25-11 ISO 7-1	318 12.50	44.7 98.5
	125A 5	483 19.00	260 10.20	229 9.00	130 5.10	1.25-11 ISO 7-1	318 12.50	44.7 98.5
	150A 6	483 19.00	260 10.20	229 9.00	144 5.70	1.25-11 ISO 7-1	318 12.50	46.3 102.1
	200A 8	483 19.00	260 10.20	229 9.00	172 6.80	1.25-11 ISO 7-1	318 12.50	50.2 110.7

4.3 DIMENSIONS (Continued)

JIS Dimensions

Series 731-D with JIS 10K Flange




350A – 600A mm

Size		Dimensions						Approx. Weight (Each)	
System Side Grooved	Pump Side x Flange ANSI Class 150	L	L1	H1	H2	Thread Size	E		
Nominal Size		mm inches	mm inches	mm inches	mm inches		mm inches	kg lb	
250A 10	x 6	150A	584 23.00	315 12.40	279 11.00	144 5.70	1.25-11 ISO 7-1	395 15.60	68.3 150.6
		200A	584 23.00	315 12.40	279 11.00	172 6.80	1.25-11 ISO 7-1	395 15.60	72.5 159.9
	250A	584 23.00	315 12.40	279 11.00	205 8.10	1.25-11 ISO 7-1	395 15.60	78.0 172.0	
300A 12	x 8	200A	686 27.00	392 15.40	335 13.20	172 6.80	1.25-11 ISO 7-1	472 18.60	111.3 245.4
		250A	686 27.00	392 15.40	335 13.20	205 8.10	1.25-11 ISO 7-1	472 18.60	118.1 260.3
	300A	686 27.00	392 15.40	335 13.20	241 9.50	1.25-11 ISO 7-1	472 18.60	123.9 273.2	

4.4 DIMENSIONS

AS Dimensions

Series 731-D with
Australian Standard Flange Table "E"



3 – 12"/80 – 300 mm


Size		Dimensions							Approx. Weight (Each)
System Side Grooved	Pump Side x Flange ANSI Class 150	L	L1	H1	H2	Thread Size	E		
Nominal Size		mm	mm	mm	mm		mm	kg	
mm	inches	mm	mm	mm	mm		mm	lb	
inches		inches	inches	inches	inches		inches		
76.1 mm	x 50	279	160	140	83	1-11 ISO 7-1	190	9.1	
	2	11.00	6.30	5.50	3.30		7.50	20.1	
80	x 50	279	160	140	83	1-11 ISO 7-1	190	9.1	
		2	11.00	6.30	5.50		3.30	7.50	20.1
	76.1 mm	279	160	140	93	1-11 ISO 7-1	190	12.6	
		2	11.00	6.30	5.50		3.70	7.50	27.7
80	x 3	279	160	140	101	1-11 ISO 7-1	190	12.6	
		2	11.00	6.30	5.50		4.00	7.50	27.7
100	x 76.1 mm	330	187	165	93	1-11 ISO 7-1	222	15.0	
		4	13.00	7.40	6.50		3.70	8.70	31.6
		80	330	187	165		101	1-11 ISO 7-1	222
3	13.00	7.40	6.50	4.00	8.70	31.6			
100	x 100	330	187	165	116	1-11 ISO 7-1	222	15.7	
		4	13.00	7.40	6.50		4.60	8.70	34.6
		125	381	213	191		101	1.25-11 ISO 7-1	250
3	15.00	8.40	7.50	4.00	9.80	44.0			
125	x 100	381	213	191	116	1.25-11 ISO 7-1	250	22.2	
		4	15.00	8.40	7.50		4.60	9.80	49.0
		125	381	213	191	130	1.25-11 ISO 7-1	250	23.7
5	15.00	8.40	7.50	5.10	9.80	52.3			
150	x 100 ¹	406	229	203	116	1.25-11 ISO 7-1	279	29.0	
		4	16.00	9.00	8.00		4.60	11.00	64.0
		125	406	229	203	130	1.25-11 ISO 7-1	279	30.0
		5	16.00	9.00	8.00	5.10		11.00	67.3
150	x 150	406	229	203	144	1.25-11 ISO 7-1	279	31.9	
		6	16.00	9.00	8.00		5.70	11.00	70.3
		200	483	260	229	130	1.25-11 ISO 7-1	318	44.7
5	19.00	10.20	9.00	5.10	12.50	98.5			
200	x 150	483	260	229	144	1.25-11 ISO 7-1	318	46.3	
		6	19.00	10.20	9.00		5.70	12.50	102.1
		200	483	260	229	172	1.25-11 ISO 7-1	318	50.2
8	19.00	10.20	9.00	6.80	12.50	110.7			
250	x 150 ¹	584	315	279	144	1.25-11 ISO 7-1	395	68.3	
		6	23.00	12.40	11.00		5.70	15.60	150.6
		200	584	315	279	172	1.25-11 ISO 7-1	395	72.5
		8	23.00	12.40	11.00	6.80		15.60	159.9
250	x 250	584	315	279	205	1.25-11 ISO 7-1	395	78.0	
		10	23.00	12.40	11.00		8.10	15.60	172.0
		300	686	392	335	172	1.25-11 ISO 7-1	472	111.3
8	27.00	15.40	13.20	6.80	18.60	245.4			
300	x 250	686	392	335	205	1.25-11 ISO 7-1	472	118.1	
		10	27.00	15.40	13.20		8.10	18.60	260.3
		300	686	392	335	241	1.25-11 ISO 7-1	472	123.9
12	27.00	15.40	13.20	9.50	18.60	273.2			

¹ Available with No. 50 Concentric Reducer and the appropriate coupling for additional size needs. Contact Victaulic for details.

4.5 DIMENSIONS

Support and tap boss location

Series 731-D Suction Diffuser



Inlet Size inches mm	Boss Tap Two Places			Support Locations Three Places			
	A inches mm	B inches mm	C inches mm	D ² inches mm	E ² inches mm	F inches mm	G inches mm
3 80	1.88 47.8	3.25 82.6	1.00 25.4	1.30 33.0	1.80 45.7	2.10 53.3	2.30 58.4
4 100	2.70 68.6	3.25 82.6	1.00 25.4	1.30 33.0	1.80 45.7	2.70 68.6	2.90 73.7
5 125	3.02 76.7	4.25 108.0	1.50 38.1	1.80 45.7	2.70 68.6	3.35 85.1	3.83 58.4
6 150	3.52 89.4	5.50 114.3	1.50 38.1	1.80 45.7	2.70 68.6	4.00 101.6	4.52 114.8
8 200	4.45 113.0	5.00 127.0	1.50 38.1	1.80 45.7	2.70 68.6	5.18 131.6	5.70 144.8
10 250	5.50 139.7	6.50 165.1	1.50 38.1	1.80 45.7	2.70 68.6	6.45 163.8	6.97 177.0
12 300	6.48 164.6	8.00 203.2	1.50 38.1	1.80 45.7	2.70 68.6	7.65 194.3	8.17 207.5

² Listed as diameters.

4.6 DIMENSIONS

Assembly Clearance

The recommended access requirements and support leg pipe diameters are listed in the following table. The recommended support leg in pipe diameters is based on Schedule 40 pipe. Reference the illustration on the next page.


Recommended Minimum Clearance Required to Remove Diffuser Basket										
ANSI				DIN			GB			
Size inches mm		Clearance "C" inches mm	Rec. Support Leg Pipe Diameter ³ inches	Size mm inches	Clearance "C" mm inches	Rec. Support Leg Pipe Diameter ³ inches	Size mm inches	Clearance "C" mm inches	Rec. Support Leg Pipe Diameter ³ inches	
3 80	x	2 50	1 1/4	76.1 mm	50 2	1 1/4	76.1 mm	50 2	1 1/4	
		2.5 65			152 6.00			152 6.00		
		3 80			152 6.00			152 6.00		
4 100	x	2.5 65	1 1/4	76.1 mm	80 3	1 1/4	76.1 mm	80 3	1 1/4	
		3 80			178 7.00			178 7.00		
		4 100			178 7.00			178 7.00		
5 125	x	3 80	2	139.7 mm	76.1 mm	2	139.7 mm	76.1 mm	2	
		4 100			203 8.00			203 8.00		
		5 125			203 8.00			203 8.00		
6 150	x	4 100	2	139.7 mm	80 3	2	139.7 mm	80 3	2	
		5 125			203 8.00			203 8.00		
		6 150			241 9.50			241 9.50		
8 200	x	5 125	2	150 mm	100 4	2	150 mm	100 4	2	
		6 150			203 8.00			203 8.00		
		8 200			305 12.00			305 12.00		
10 250	x	6 150	2	200 mm	139.7 mm	2	200 mm	139.7 mm	2	
		8 200			241 9.50			241 9.50		
		10 250			406 16.00			406 16.00		
12 300	x	8 200	2	250 mm	200 8	2	250 mm	200 8	2	
		10 250			305 12.00			305 12.00		
		12 300			457 18.00			457 18.00		
3	Based on Schedule 40 pipe diameter.			250 mm	150 6		250 mm	150 6		
				200 mm	200 8		200 mm	200 8		
				250 mm	250 10		250 mm	250 10		
3	Based on Schedule 40 pipe diameter.			300 mm	200 8		300 mm	200 8		
				250 mm	250 10		250 mm	250 10		
				300 mm	300 12		300 mm	300 12		

4.6 DIMENSIONS (Continued)

Assembly Clearance

Recommended Minimum Clearance Required to Remove Diffuser Basket										
JIS				AS Table "E"						
Size mm inches		Clearance "C" mm inches	Rec. Support Leg Pipe Diameter ³ inches	Size mm inches		Clearance "C" mm inches	Rec. Support Leg Pipe Diameter ³ inches			
76.1 mm	x	50A 2	152 6.00	1/4	76.1 mm	x	50 2	152 6.00	1/4	
80A 3	x	50A 2	152 6.00	1/4	80 3	x	50 2	152 6.00	1/4	
		76.1 mm	152 6.00				76.1 mm	152 6.00		
		80A 3	152 6.00				80 3	152 6.00		
100A 4	x	76.1 mm	178 7.00	1/4	100 4	x	76.1 mm	178 7.00	1/4	
		80A 3	178 7.00				80 3	178 7.00		
		100A 4	178 7.00				100 4	178 7.00		
139.7 mm	x	76.1 mm	203 8.00	2	125 5	x	80 3	203 8.00	2	
125A 5	x	76.1 mm	203 8.00	2	150 6	x	100 4	203 8.00		2
		80A 3	203 8.00				125 5	203 8.00		
		100A 4	203 8.00				100 4	241 9.50		
		125A 5	203 8.00				125 5	241 9.50		
150A 6	x	100A 4	241 9.50	2	200 8	x	150 6	241 9.50	2	
		139.7 mm	241 9.50				125 5	305 12.00		
		125A 5	241 9.50				150 6	305 12.00		
		150A 6	241 9.50				200 8	305 12.00		
200A 8	x	139.7 mm	305 12.00	2	250 10	x	150 6	406 16.00	2	
		125A 5	305 12.00				200 8	406 16.00		
		150A 6	305 12.00				250 10	406 16.00		
		200A 8	305 12.00				300 12	457 18.00		
250A 10	x	150A 6	406 16.00	2	300 12	x	200 8	457 18.00	2	
		200A 8	406 16.00				250A 10	457 18.00		
		250A 10	406 16.00				300A 12	457 18.00		
300A 12	x	200A 8	457 18.00	2	300A 12	x	200 8	457 18.00	2	
		250A 10	457 18.00				250A 10	457 18.00		
		300A 12	457 18.00				300A 12	457 18.00		

³ Based on Schedule 40 pipe diameter.



5.0 PERFORMANCE

Flow Characteristics

Formulas for C_v Values:

$$\Delta P = \frac{Q^2}{C_v^2}$$

$$Q = C_v \times \sqrt{\Delta P}$$

Where:

Q = Flow (GPM)

ΔP = Pressure Drop (psi)

C_v = Flow Coefficient

Formulas for K_v Values:

$$\Delta P = \frac{Q^2}{K_v^2}$$

$$Q = K_v \times \sqrt{\Delta P}$$

Where:

Q = Flow (m³/hr)

ΔP = Pressure Drop (Bar)



K_v = Flow Coefficient

C_v values for flow of water at +60°F/+16°C through a fully open valve.

Size		Flow Data	C_v K_v
Actual Outside Diameter	inches mm		
3.000 76.1	x	2.375	79
		60.3	68
3.500 88.9	x	2.375	79
		60.3	68
		3.000	79
		76.1	68
4.500 114.3	x	3.500	90
		88.9	79
		3.000	144
		76.1	125
5.500 139.7	x	3.500	144
		88.9	125
		4.500	161
		114.3	139
5.563 141.3	x	3.000	206
		76.1	178
		3.500	206
		88.9	178
		4.500	232
6.625 168.3	x	114.3	200
		5.563	251
		141.3	217
		4.500	295
		114.3	255
8.625 219.1	x	5.500	361
		139.7	312
		5.563	361
		141.3	312
		6.625	361
10.750 273.0	x	168.3	312
		6.625	509
		168.3	440
		8.625	509
		219.1	440
12.750 323.9	x	8.625	575
		219.1	497
		10.750	642
		273.0	555
		12.750	821
12.750 323.9	x	168.3	710
		8.625	917
		219.1	793
		10.750	1003
12.750 323.9	x	273.0	867
		8.625	1352
		219.1	1170
12.750 323.9	x	10.750	1352
		273.0	1170
12.750 323.9	x	12.750	1445
		323.9	1249

5.0 PERFORMANCE (Continued)

Flow Characteristics



6.0 NOTIFICATIONS

WARNING

- Always depressurize and drain system before disassembly. Failure to do so could result in serious personal injury, property damage, joint leakage or joint separation.

7.0 REFERENCE MATERIALS

[05.01: Victaulic Seal Selection Guide](#)

[24.01: Victaulic Pipe Preparation Tools](#)

[I-100: Victaulic Field Installation Handbook](#)

User Responsibility for Product Selection and Suitability

Each user bears final responsibility for making a determination as to the suitability of Victaulic products for a particular end-use application, in accordance with industry standards and project specifications, and the applicable building codes and related regulations as well as Victaulic performance, maintenance, safety, and warning instructions. Nothing in this or any other document, nor any verbal recommendation, advice, or opinion from any Victaulic employee, shall be deemed to alter, vary, supersede, or waive any provision of Victaulic Company's standard conditions of sale, installation guide, or this disclaimer.

Intellectual Property Rights

No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Victaulic or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right. The terms "Patented" or "Patent Pending" refer to design or utility patents or patent applications for articles and/or methods of use in the United States and/or other countries.

Note

This product shall be manufactured by Victaulic or to Victaulic specifications. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.

Installation

Reference should always be made to the Victaulic installation handbook or installation instructions of the product you are installing. Handbooks are included with each shipment of Victaulic products, providing complete installation and assembly data, and are available in PDF format on our website at www.victaulic.com.

Warranty

Refer to the Warranty section of the current Price List or contact Victaulic for details.

Trademarks

Victaulic and all other Victaulic marks are the trademarks or registered trademarks of Victaulic Company, and/or its affiliated entities, in the U.S. and/or other countries.