

# Victaulic® FireLock™ Installation-Ready™ Rigid Couplings

## Style 009N and Style 109



Patented



Patented

### 1.0 PRODUCT DESCRIPTION

#### Available Sizes

- Style 009N: 1 ¼ – 12"/DN32 – DN300
- Style 109: 1 ¼ – 2 ½"/DN32 – 73.0 mm

#### Pipe Material

- Schedule 10, Schedule 40 or specialty carbon steel pipe listed in Section 5. For use with alternative materials and wall thicknesses please contact Victaulic
- Carbon Steel
- Stainless Steel
- For exceptions reference section 6.0 Notifications

#### Maximum Working Pressure

- Up to 365 psi/2517 kPa

#### Function

- Joins carbon steel pipe with grooved ends conforming to [publication 25.01](#)
- Provides a rigid pipe joint designed to restrict axial or angular movement

### 2.0 CERTIFICATION/LISTINGS



C104-1a/36

EN 10311  
Regulation (EU)  
No. 305/2011

ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.

System No.		Location	
Submitted By		Date	

Spec Section		Paragraph	
Approved		Date	

### 3.0 SPECIFICATIONS – MATERIAL

---

**Housing:** Ductile iron conforming to ASTM A 536, Grade 65-45-12. Ductile iron conforming to ASTM A 395, Grade 65-45-15, is available upon special request.

**Housing Coating: (specify choice)**

- Orange enamel (North America, Asia Pacific)
- Red enamel (Europe)
- Optional for Style 009N: Hot dipped galvanized

**Gasket: (specify choice)**

**Grade “E” EPDM (Type A) Vic-Plus™ Pre-lubricated Gasket**

EPDM (Violet Color Code). Applicable for wet and dry (oil-free air) fire protection systems only. Listed/Approved for continuous use in wet and dry systems. Listed/Approved for dry systems at -40°F/-40°C and above. Not compatible for use with hot water services or steam services.

**NOTES**

- Reference should always be made to [publication I-100](#), Victaulic Field Installation Handbook for gasket lubrication instructions.
- Services listed are General Service Guidelines only. It should be noted that there are services for which these gaskets are not compatible. Reference should always be made to [publication 05.01](#), Victaulic Gasket Selection Guide for specific gasket service guidelines and for a listing of services which are not compatible.

**Bolts/Nuts: (specify choice)**

Standard: Carbon steel oval neck track bolts meeting the mechanical property requirements of ASTM A449 (imperial) and ISO 898-1 Class 9.8 (M10-M16) Class 8.8 (M20 and greater). Carbon steel hex nuts meeting the mechanical property requirements of ASTM A563 Grade B (imperial) and ASTM A563M Class 9 (metric). Track bolts and hex nuts are zinc electroplated per ASTM B633 Fe/Zn 5, finish Type III (imperial) or Type II (metric).


Optional for Style 009N: Stainless steel oval neck track bolts meeting the requirements of ASTM F593, Group 2 (316 stainless steel), condition CW. Stainless steel Heavy Hex nuts meeting the requirements of ASTM F594, Group 2 (316 stainless steel), condition CW, with galling-resistant coating.<sup>1</sup>

<sup>1</sup> Optional bolts/nuts are available in imperial size only.

**Coupling Linkage:** High Strength Steel with comparable physical properties to that of the Track Bolt (ASTM A449). Linkage is zinc electroplated per ASTM B633 Fe/Zn 5, Type III Finish.

## 4.0 DIMENSIONS

### Style 009N Two-Bolt Installation-Ready Coupling



Size		Maximum Working Pressure <sup>2</sup>	Maximum End Load <sup>2</sup>	Allow. Pipe End Separation <sup>3</sup>	Qty.	Bolt/Nut Size	Dimensions					Weight Approx. (Each)
Nominal	Actual Outside Diameter						Pre-assembled		Joint Assembled		Z	
							X	Y	X	Y		
inches DN	inches mm	psi kPa	lb N	inches mm	inches mm	inches mm	inches mm	inches mm	inches mm	lb kg		
1 ¼ DN32	1.660 42.4	365 2517	790 3514	0.10 2.54	2	¾ × 2 M10 x 51	3.13 79	5.00 127	2.75 70	5.00 127	2.00 51	1.4 0.6
1 ½ DN40	1.900 48.3	365 2517	1035 4604	0.10 2.54	2	¾ × 2 M10 x 51	3.38 86	5.13 130	3.00 76	5.13 130	2.00 51	1.5 0.7
2 DN50	2.375 60.3	365 2517	1617 7193	0.12 3.05	2	¾ × 2 ½ M10 x 63	4.00 102	5.63 143	3.50 89	5.63 143	2.00 51	1.9 0.9
2 ½	2.875 73.0	365 2517	2370 10542	0.12 3.05	2	¾ × 2 ½ M10 x 63	4.50 114	6.13 156	4.00 102	6.13 156	2.00 51	2.1 1.0
DN65	3.000 76.1	365 2517	2580 11476	0.12 3.05	2	¾ × 2 ½ M10 x 63	4.63 118	6.00 152	4.13 105	6.13 156	2.00 51	2.1 1.0
3 DN80	3.500 88.9	365 2517	3512 15622	0.12 3.05	2	¾ × 2 ½ M10 x 63	5.13 130	6.75 171	4.63 117	6.75 171	2.00 51	2.3 1.0
4 DN100	4.500 114.3	365 2517	5805 25822	0.17 4.32	2	¾ × 2 ½ M10 x 63	6.00 152	7.88 200	5.63 143	7.50 191	2.13 54	2.9 1.3
	4.250 108.0	365 2517	5178 23020	0.17 4.32	2	¾ × 2 ½ M10 x 63	5.63 152	7.38 187	5.38 137	7.38 187	2.13 54	3.1 1.4
5	5.563 141.3	365 2517	8872 39456	0.17 4.32	2	½ × 3 M12 x 76	7.25 184	9.25 235	6.75 171	9.13 232	2.25 57	5.0 2.3
	5.250 133.0	365 2517	7901 35106	0.17 4.32	2	½ × 3 M12 x 76	6.63 168	9.00 229	6.38 162	9.00 229	2.25 57	4.8 2.2
DN125	5.500 139.7	365 2517	8672 38529	0.17 4.32	2	½ × 3 M12 x 76	6.88 175	9.25 235	6.75 171	9.13 232	2.25 57	4.9 2.2
6 DN150	6.625 168.3	365 2517	12582 44469	0.17 4.32	2	½ × 3 ¼ M12 x 83	8.38 213	10.38 264	7.88 200	10.13 257	2.25 57	6.0 2.7
	6.250 159.0	365 2517	11198 49753	0.17 4.32	2	½ × 3 ¼ M12 x 83	7.88 200	10.00 254	7.38 187	9.88 251	2.25 57	5.6 2.5
	6.500 165.1	365 2517	12112 53813	0.17 4.32	2	½ × 3 ¼ M12 x 83	8.00 203	10.25 260	7.75 197	10.13 257	2.25 57	6.0 2.7
8 DN200	8.625 219.1	365 2517	21326 94863	0.17 4.32	2	¾ × 4 M16 x 101	10.88 276	13.38 340	10.25 260	13.13 333	2.50 64	11.4 5.2
	8.500 216.0	365 2517	20712 55968	0.17 4.32	2	¾ × 4 M16 x 101	10.63 270	13.25 337	10.25 260	10.13 257	2.63 67	11.4 5.2
10 DN250	10.750 273.0	300 2068	27229 121121	0.25 6.4	2	7/8 × 6 ½ M22 x 165	13.75 349	17.00 432	13.25 337	17.13 435	2.75 70	22.6 10.3
12 DN300	12.750 323.9	300 2068	38303 170380	0.25 6.4	2	7/8 × 6 ½ M22 x 165	16.00 406	19.00 483	15.50 394	19.13 486	2.75 70	27.6 12.5

<sup>2</sup> Working Pressure and End Load are total, from all internal and external loads, based on standard weight (ANSI) steel pipe, standard roll or cut grooved in accordance with Victaulic specifications. See the Listings/Approvals section of this publication for ratings on other pipe.


<sup>3</sup> The allowable pipe separation dimension shown is for system layout purposes only. Style 009N couplings are considered rigid connections and will not accommodate expansion or contraction of the piping system.

#### NOTES

- When assembling Style 009N or Style 109 couplings onto end caps, take additional care to make certain the end cap is fully seated against the gasket end stop. For Style 009N or Style 109 couplings, use FireLock No. 006 end caps containing the "EZ" marking on the inside face or No. 60 end caps containing the "QV EZ" marking on the inside face. Non-Victaulic end cap products shall not be used with Style 009N or Style 109 couplings. IMPORTANT: Gaskets intended for the Style 009 or Style 009V couplings cannot be used with the Style 009N or Style 109 coupling. There is no interchanging of gaskets or housings between coupling styles.
- Use Of FlushSeal Gaskets For Dry Pipe Systems** Style 009N or Style 109 couplings are supplied with Grade "E" Type A gaskets. These gaskets include an integral pipe stop, that once installed provides the similar benefits as a FlushSeal gasket for dry pipe systems. It should be noted that standard Victaulic FlushSeal gaskets cannot be used with the Style 009N or Style 109 couplings.

## 4.1 DIMENSIONS

### Style 109 One-Bolt *Installation-Ready* Coupling



Style 109 Pre-Assembled

Style 109 Joint Assembled

Size		Maximum Working Pressure <sup>4</sup>	Maximum End Load <sup>4</sup>	Pipe End Separation Allowable <sup>5</sup>	Bolt/Nut		Dimensions								Weight	
Nominal	Actual Outside Diameter				Qty.	Size	Pre-assembled				Joint Assembled					Approx. (Each)
							YL	YB	X	Z	YL	YB	X	Z		
inches mm	inches mm	psi kPa	lb N	inches mm	inches mm	inches mm	inches mm	inches mm	inches mm	inches mm	inches mm	inches mm	inches mm	inches mm	lb kg	
1 ¼ DN32	1.660 42.4	365 2517	790 3514	0.10 2.54	1	¾ x 2 ¼ M10 x 57	1.88 48	2.50 64	3.13 79	1.88 48	1.88 48	2.63 67	2.75 70	1.88 48	1.4 0.6	
1 ½ DN40	1.900 48.3	365 2517	1035 4604	0.10 2.54	1	¾ x 2 ¼ M10 x 57	2.00 51	2.63 67	3.25 83	1.88 48	2.00 51	2.75 70	3.00 76	1.88 48	1.5 0.7	
2 DN50	2.375 60.3	365 2517	1616 7193	0.12 3.05	1	¾ x 2 ½ M10 x 63	2.25 57	2.88 73	3.88 98	2.00 51	2.25 57	3.13 79	3.50 89	2.00 51	1.8 0.8	
2 ½	2.875 73.0	365 2517	2370 10542	0.12 3.05	1	¾ x 2 ½ M10 x 63	2.50 64	3.13 79	4.38 111	2.00 51	2.50 64	3.38 86	3.88 98	2.00 51	2.1 0.9	

<sup>4</sup> Working Pressure and End Load are total, from all internal and external loads, based on standard weight (ANSI) steel pipe, standard roll or cut grooved in accordance with Victaulic specifications. See the Listings/Approvals section of this publication for ratings on other pipe.

<sup>5</sup> The allowable pipe separation dimension shown is for system layout purposes only. Style 109 couplings are considered rigid connections and will not accommodate expansion or contraction of the piping system.

#### NOTES

- When assembling Style 009N or Style 109 couplings onto end caps, take additional care to make certain the end cap is fully seated against the gasket end stop. For Style 009N or Style 109 couplings, use FireLock No. 006 end caps containing the "EZ" marking on the inside face or No. 60 end caps containing the "QV EZ" marking on the inside face. Non-Victaulic end cap products shall not be used with Style 009N or Style 109 couplings. IMPORTANT: Gaskets intended for the Style 009 or Style 009V couplings cannot be used with the Style 009N or Style 109 coupling. There is no interchanging of gaskets or housings between coupling styles.
- Use Of FlushSeal Gaskets For Dry Pipe Systems** Style 009N or Style 109 couplings are supplied with Grade "E" Type A gaskets. These gaskets include an integral pipe stop, that once installed provides the similar benefits as a FlushSeal gasket for dry pipe systems. It should be noted that standard Victaulic FlushSeal gaskets and cannot be used with the Style 009N or Style 109 couplings.

## 5.0 PERFORMANCE

### Style 009N Two-Bolt *Installation-Ready Coupling Listings/Approvals*<sup>6</sup>

The information provided below is based on the latest listing and approval data at the time of publication. Listings/Approvals are subject to change and/or additions by the approval agencies. Contact Victaulic for performance on other pipe and the latest listings and approvals.

Size		cULus <sup>11</sup>		FM <sup>11</sup>		VdS	LPCB
Nominal inches DN	Actual Outside Diameter inches mm	Sch. 10 psi kPa bar	Sch. 40 psi kPa bar	Sch. 10 psi kPa bar	Sch. 40 psi kPa bar	psi kPa bar	psi kPa bar
1 ¼ DN32	1.660 42.4	365 2517 25	365 2517 25	363 2503 25	363 2503 25	363 2500 25	363 2500 25
1 ½ DN40	1.900 48.3	365 2517 25	365 2517 25	363 2503 25	363 2503 25	363 2500 25	363 2500 25
2 DN50	2.375 60.3	365 2517 25	365 2517 25	363 2503 25	363 2500 25	363 2500 25	363 2500 25
2 ½	2.875 73.0	365 2517 25	365 2517 25	363 2503 25	363 2500 25	363 2500 25	363 2500 25
DN65	3.000 76.1	365 <sup>7</sup> 2517 <sup>7</sup> 25 <sup>7</sup>	N/A	363 <sup>8</sup> 2503 <sup>8</sup> 25 <sup>8</sup>	N/A	363 2500 25	363 2500 25
3 DN80	3.500 88.9	365 2517 25	365 2517 25	363 2503 25	363 2503 25	363 2500 25	363 2500 25
4 DN100	4.500 114.3	365 2517 25	365 2517 25	363 2503 25	363 2503 25	363 2500 25	363 2500 25
	4.250 108.0	N/A	N/A	363 2503 25	363 2503 25	N/A	N/A
5	5.563 141.3	290 2000 20	365 2517 25	363 2503 25	363 2503 25	232 1600 16	363 2500 25
	5.250 133.0	N/A	N/A	363 <sup>8</sup> 2503 <sup>8</sup> 25	N/A	N/A	N/A
DN125	5.500 139.7	290 <sup>9</sup> 2000 <sup>9</sup> 20 <sup>9</sup>	N/A	363 <sup>8</sup> 2503 <sup>8</sup> 25 <sup>8</sup>	N/A	232 1600 25	363 2500 25
6 DN150	6.625 168.3	300 2068 20	365 2517 25	363 2503 25 <sup>7</sup>	363 2503 25	232 1600 16	363 2500 25
	6.250 159.0	N/A	N/A	363 <sup>8</sup> 2503 <sup>8</sup> 25	N/A	N/A	N/A
	6.500 165.1	290 <sup>10</sup> 2000 <sup>10</sup> 20	N/A	363 <sup>8</sup> 2503 <sup>8</sup> 25 <sup>8</sup>	N/A	N/A	363 2500 25

<sup>6</sup> Listed/Approved for continuous use in wet and dry systems. Listed/Approved for dry systems -40° F/C and above. Please see the Victaulic [Installation Manual I-009N](#) for details concerning when supplemental lubrication is required.

<sup>7</sup> cULus listed for DIN 2458 (EN 10220) 2.6 mm pipe wall.

<sup>8</sup> FM approved for BS 1387 (EN 10255) Medium 3.6 mm pipe wall.

<sup>9</sup> cULus listed for EN 10220 4.0 mm pipe wall.

<sup>10</sup> cULus listed for EN 10255 4.5 mm pipe wall.

<sup>11</sup> With optional stainless steel fasteners, cULus Listed to 175psi/1207 kPa/12 bar and FM Approved to the FM ratings shown in the above table. The stainless steel fasteners have a marking designation of "316" on the end face of the bolt.

<sup>12</sup> cUL listed to 250 psi/1720 kPa /17 bar.

## 5.0 PERFORMANCE (CONTINUED)

### Style 009N Two-Bolt *Installation-Ready Coupling Listings/Approvals*<sup>6</sup>

The information provided below is based on the latest listing and approval data at the time of publication. Listings/Approvals are subject to change and/or additions by the approval agencies. Contact Victaulic for performance on other pipe and the latest listings and approvals.

Size		cULus <sup>11</sup>		FM <sup>11</sup>		VdS	LPCB
Nominal inches DN	Actual Outside Diameter inches mm	Sch. 10 psi kPa bar	Sch. 40 psi kPa bar	Sch. 10 psi kPa bar	Sch. 40 psi kPa bar	psi kPa bar	psi kPa bar
8 DN200	8.625 219.1	300 2068 20	365 2517 25	363 2503 25	363 2503 25	232 1600 16	363 2500 25
	8.500 216.0	290 2000 20	N/A	363 <sup>8</sup> 2503 <sup>8</sup> 25 <sup>7</sup>	N/A	N/A	N/A
10 DN250	10.750 273.0	300 2068 20	300 2068 20	300 2068 20	300 2068 20	N/A	N/A
12 DN300	12.750 323.9	300 <sup>12</sup> 2068 <sup>12</sup> 20 <sup>12</sup>	300 2068 25	250 1720 17	300 2068 20	N/A	N/A

<sup>6</sup> Listed/Approved for continuous use in wet and dry systems. Listed/Approved for dry systems -40° F/C and above. Please see the Victaulic [Installation Manual I-009N](#) for details concerning when supplemental lubrication is required.

<sup>7</sup> cULus listed for DIN 2458 (EN 10220) 2.6 mm pipe wall.

<sup>8</sup> FM approved for BS 1387 (EN 10255) Medium 3.6 mm pipe wall.

<sup>9</sup> cULus listed for EN 10220 4.0 mm pipe wall.

<sup>10</sup> cULus listed for EN 10255 4.5 mm pipe wall.

<sup>11</sup> With optional stainless steel fasteners, cULus Listed to 175psi/1207 kPa/12 bar and FM Approved to the FM ratings shown in the above table. The stainless steel fasteners have a marking designation of "316" on the end face of the bolt.

<sup>12</sup> cUL listed to 250 psi/1720 kPa /17 bar.

## 5.1 PERFORMANCE

### Style 109 One-Bolt *Installation-Ready Coupling Listings/Approvals*<sup>13</sup>

The information provided below is based on the latest listing and approval data at the time of publication. Listings/Approvals are subject to change and/or additions by the approvals agencies. Contact Victaulic for performance on other pipe and the latest listings and approvals.

Size		cULus		FM	
Nominal inches DN	Actual Outside Diameter inches mm	Sch. 10 psi kPa bar	Sch. 40 psi kPa bar	Sch. 10 psi kPa bar	Sch. 40 psi kPa bar
1 ¼ DN32	1.660 42.4	365 2517 25	365 2517 25	365 2517 25	365 2517 25
1 ½ DN40	1.900 48.3	365 2517 25	365 2517 25	365 2517 25	365 2517 25
2 DN50	2.375 60.3	365 2517 25	365 2517 25	365 2517 25	365 2517 25
2 ½	2.875 73.0	365 2517 25	365 2517 25	365 2517 25	365 2517 25

<sup>13</sup> Listed/Approved for continuous use in wet and dry systems. Listed/Approved for dry systems -40° F/C and above. Please see the Victaulic [Installation Manual I-109](#) for details concerning when supplemental lubrication is required.

## 5.2 PERFORMANCE

### Specialty Pipe Style 009N Two-Bolt *Installation-Ready* Coupling Listings/Approvals

Pipe Type	Size  inches DN	Pressure Rating	
		cULus psi kPa bar	FM psi kPa bar
EF	1 ¼ – 4 DN32 – DN100	300 2068 20	N/A
EL	1 ¼ – 2 DN32 – DN50	300 2068 20	300 2068 20
ET40	1 ¼ – 2 DN32 – DN50	300 2068 20	N/A
EZF	3 – 4 DN80 – DN100	300 2068 20	N/A
EZT	1 ¼ – 2 DN32 – DN50	300 2068 20	300 2068 20
FF	1 ½ – 4 DN40 – DN100	300 2068 20	N/A
GL	1 ¼ – 2 DN32 – DN50	300 2068 20	300 2068 20
MF	1 ¼ – 4 DN32 – DN100	300 2068 20	300 2068 20
	6 DN150	175 1205 12	175 1205 12
MT	1 ¼ – 2 DN32 – DN50	300 2068 20	300 2068 20
MLT	1 ¼ – 2 DN32 – DN50	N/A	300 2068 20
TF	2 ½ – 4 73.0 mm – DN100	N/A	300 2068 20
WG5, WG5E, WF5, WG7, WG7E, WL7	1 ¼ – 4 DN32 – DN100	175 1205 12	300 2068 20
WLS	1 ¼ – 2 DN32 – DN50	300 2068 20	300 2068 20

#### NOTES

- EF = EDDY FLOW steel pipe manufactured by Bull Moose Tube Co.
- EL = EDDYLITE steel pipe manufactured by Bull Moose Tube Co.
- ET40 = Eddythread 40 steel pipe manufactured by Bull Moose Tube Co.
- EZF = EZ-Flow steel pipe manufactured by Northwest Pipe Co.
- EZT = EZ-Thread steel pipe manufactured by Youngstown Tube Co.
- FF = Fire-Flo steel pipe manufactured by Youngstown Tube Co.
- GL = GL steel pipe manufactured by Wheatland Tube Co.
- MF = Mega-Flow steel pipe manufactured by Wheatland Tube Co.
- MT = Mega-Thread steel pipe manufactured by Wheatland Tube Co.
- MLT = MLT steel pipe manufactured by Wheatland Tube Co
- TF = Tex-Flow steel pipe manufactured by Tex-Tube Co.
- WG5, WG5E, WF5 = WGalweld 5, WGalweld 5E, WFlow 5 steel pipe manufactured by Wuppermann Stahl GmbH.
- WG7, WG7E, WL7 = WGalweld 7, Wgalweld 7E, WLight 7 steel pipe manufactured by Wuppermann Stahl GmbH
- WLS = WLS steel pipe manufactured by Wheatland Tube Co.

### 5.3 PERFORMANCE

#### Specialty Pipe Style 109 One-Bolt *Installation-Ready* Coupling Listings/Approvals

Pipe Type	Size	Pressure Rating	
	inches	cULus	FM
	DN	psi kPa bar	psi kPa bar
EF	1 ¼ – 2 ½ DN32 – 73.0 mm	N/A	300 2068 20
	1 ½ – 2 ½ DN40 – 73.0 mm	300 2068 20	N/A
Easy-Flow	1 ¼ – 2 DN32 – DN50	N/A	300 2068 20
EL	1 ¼ – 2 DN32 – DN50	N/A	300 2068 20
ET40	1 ¼ – 2 DN32 – DN50	300 2068 20	300 2068 20
EZT	1 ¼ – 2 DN32 – DN50	N/A	300 2068 20
	1 ½ – 2 DN40 – DN50	300 2068 20	N/A
FF	1 ½ – 2 ½ DN40 – 73.0 mm	300 2068 20	300 2068 20
GL	1 ¼ – 2 DN32 – DN50	N/A	300 2068
MF	1 ¼ – 2 ½ DN32 – 73.0 mm	300 2068 20	300 2068 20
MT	1 ¼ – 2 DN32 – DN50	300 2068 20	300 2068 20
MLT	1 ¼ – 2 DN32 – DN50	300 2068 20	300 2068 20
TF	2 ½ 73.0 mm	N/A	300 2068 20
WG7, WG7E	1 ¼ – 2 DN32 – DN50	N/A	300 2068 20
WLS	1 ¼ – 2 DN32 – DN50	N/A	300 2068 20


**NOTES**

- EF = EDDY FLOW steel pipe manufactured by Bull Moose Tube Co.
- Easy-Flow = Easy-Flow steel pipe manufactured by Borusan Mannesmann Boru.
- EL = EDDYLITE steel pipe manufactured by Bull Moose Tube Co.
- ET40 = Eddythread 40 steel pipe manufactured by Bull Moose Tube Co.
- EZT = EZ-Thread steel pipe manufactured by Youngstown Tube Co.
- FF = Fire-Flo steel pipe manufactured by Youngstown Tube Co.
- GL = GL steel pipe manufactured by Wheatland Tube Co.
- MF = Mega-Flow steel pipe manufactured by Wheatland Tube Co.
- MT = Mega-Thread steel pipe manufactured by Wheatland Tube Co.
- MLT = MLT steel pipe manufactured by Wheatland Tube Co.
- TF = Tex-Flow steel pipe manufactured by Tex-Tube Co.
- WG7, WG7E = WGalweld 7 and WGalweld 7E steel pipe manufactured by Wuppermann Stahl GmbH.
- WLS = WLS steel pipe manufactured by Wheatland Tube Co.



## 6.0 NOTIFICATIONS

⚠ **WARNING**



- Read and understand all instructions before attempting to install any Victaulic products.
- Always verify that the piping system has been completely depressurized and drained immediately prior to installation, removal, adjustment, or maintenance of any Victaulic products.
- Wear safety glasses, hardhat, and foot protection.

Failure to follow these instructions could result in death or serious personal injury and property damage.

- These products shall be used only in fire protection systems that are designed and installed in accordance with current, applicable National Fire Protection Association (NFPA 13, 13D, 13R, etc.) standards, or equivalent standards, and in accordance with applicable building and fire codes. These standards and codes contain important information regarding protection of systems from freezing temperatures, corrosion, mechanical damage, etc.
- The installer shall understand the use of this product and why it was specified for the particular application.
- The installer shall understand common industry safety standards and potential consequences of improper product installation.
- It is the system designer's responsibility to verify suitability of materials for use with the intended fluid media within the piping system and external environment.
- The material specifier shall evaluate the effect of chemical composition, pH level, operating temperature, chloride level, oxygen level, and flow rate on materials to confirm system life will be acceptable for the intended service.

Failure to follow installation requirements and local and national codes and standards could compromise system integrity or cause system failure, resulting in death or serious personal injury and property damage.

**NOTICE**

- Victaulic does not recommend the use of any furnace butt-welded pipe with sizes 2"/DN50 and smaller Victaulic gasketed joint products. This includes, but is not limited to, ASTM A53 Type F pipe.

## 7.0 REFERENCE MATERIALS

- [05.01: Seal Selection Guide](#)
- [25.01: Original Groove System \(OGS\) Groove Specifications](#)
- [I-009N: Installation Instructions FireLock EZ™ Rigid Coupling Style 009N](#)
- [I-100: Victaulic Field Installation Handbook](#)
- [I-109: Installation Instructions FireLock™ One-Bolt Rigid Coupling Style 109](#)
- [I-ENDCAP: Victaulic End Caps Installation Instructions](#)

### User Responsibility for Product Selection and Suitability

Each user bears final responsibility for making a determination as to the suitability of Victaulic products for a particular end-use application, in accordance with industry standards and project specifications, and the applicable building codes and related regulations as well as Victaulic performance, maintenance, safety, and warning instructions. Nothing in this or any other document, nor any verbal recommendation, advice, or opinion from any Victaulic employee, shall be deemed to alter, vary, supersede, or waive any provision of Victaulic Company's standard conditions of sale, installation guide, or this disclaimer.

### Intellectual Property Rights

No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Victaulic or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right. The terms "Patented" or "Patent Pending" refer to design or utility patents or patent applications for articles and/or methods of use in the United States and/or other countries.

### Note

This product shall be manufactured by Victaulic or to Victaulic specifications. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.

### Installation

Reference should always be made to the Victaulic installation handbook or installation instructions of the product you are installing. Handbooks are included with each shipment of Victaulic products, providing complete installation and assembly data, and are available in PDF format on our website at [www.victaulic.com](http://www.victaulic.com).

### Warranty

Refer to the Warranty section of the current Price List or contact Victaulic for details.

### Trademarks

Victaulic and all other Victaulic marks are the trademarks or registered trademarks of Victaulic Company, and/or its affiliated entities, in the U.S. and/or other countries.