




## RELN Ag-Pipe

- Range of pipe fittings available
- RTA/RMS approved Filtersock
- Available in two resins: HDPE SN8 and PVC SN20
- HDPE SN8 Ag-Pipe is ideal for general drainage applications such as sporting fields, parks and gardens
- PVC SN20 Ag-Pipe is ideal for heavy duty applications such as roads and civil engineering projects, as well as areas used by heavy vehicular traffic
- Available as Solid, Slotted and Unslotted with Filtersock in 10, 20, 50, 100 and 200. 160 available in 25.

Filtersock

Solid

Slotted



## Components:



Solid Pipe



Slotted Pipe



Filtersocked  
Pipe



Joiner



T Junction



Y Junction



End Cap

## Ag-Pipe

Corrugated Ag Pipe is a single wall corrugated drainage pipe used for subsoil drainage. Manufactured with a corrugated profile from high quality recycled and virgin resins, Ag Pipe is both strong and lightweight. All Corrugated Ag Pipe products fitted with a filter sock are RTA approved, and come packaged in a storage bag to help protect the filter sock prior to installation.

### > Ag Pipe Solid



Perfect for moving stormwater/ wastewater when drawing water away from the surrounding soil is not required.

### > Ag Pipe Slotted



Slots allow water to enter the pipe. Perfect to drain away excess groundwater and possibly surfacewater into a stormwater line, wastewater line or pit.

### > Ag Pipe Filtersock



Sock prevents unwanted sediment entering the pipe causing blockages in the line. Slotted Ag Pipe is within sock.

- Range of pipe fittings available
- RTA / RMS approved
- Available in two resins
- HDPE SN8 Ag-Pipe is ideal for general drainage applications such as sporting fields, parks and gardens
- PVC SN20 Ag-Pipe is ideal for heavy duty applications such as roads and civil engineering projects, as well as areas used by heavy vehicular traffic
- Available as Solid, Slotted and unslotted with Filtersock in 10m, 20m, 50m, 100m and 200m. 160mm available in 25m.

**Quality Assurance:** Corrugated Ag Pipe is manufactured to stringent specifications. A pipe stiffness test is carried out as part of compliance to AS2439-1-2007, and in accordance with AS/NZS1462.22, which tests the stiffness capabilities of the pipe. Pipe samples are placed within an Instron Impact / Compression Testing Unit and data is entered based on the pipe's wall thickness and weight. A series of deflection tests are then carried out to give a final reading on the stiffness of the pipe.

## > Frequently Asked Questions

### Q1. Can you buy the sock only?

A. Yes. However, the sock is only available on a 250m roll.

### Q2. How big are the slots on the pipe?

A. The slots surround the entire pipe.

### Q3. Is there a joiner on the roll?

A. Yes. The Ag-Pipe comes with a coupling.



No job too wet.