

Code EP52UMS – 52cm Undermount Rangehood

Air Extraction



bringing european quality to your home



FEATURES

- Stainless steel finish
- 3 speed motor
- 500m³ / hr extraction capacity
- Halogen down lights
- Undermount non-visible rangehood
- Under push button control
- Dishwasher safe cassette filter
- Decibel rating 52-53-56 dBA
- 150mm Flue diameter

3 SPEED MOTOR

This range hood provides the option of 3 different speed levels ensuring you have the option to use your range hood at a low, medium or high level of operation.

EXTRACTION CAPACITY

The extraction capacity of 500m³ / hr provides strength and power to this stylish range hood.

DISHWASHER SAFE CASSETTE FILTERS

The cassette filter has 5 aluminum layers, it can be placed in a dishwasher for easy cleaning and can easily be removed and re-connected from the range hood.

DECIBEL RATING

52-53-56 dBA

TIPS FOR BETTER USE

- Leave your range hood on for 15 minutes after the cooking of the food to remove all odors, steam etc.
 - The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
 - It is recommended the range hood be installed between 650mm and 750mm above the cook top
 - It is also recommended that fumes from the range hood be ducted out into the atmosphere.
 - Turn off the range hood before attempting to clean
- Installation recommended by qualified technician.**

PRODUCT DIMENSIONS

ELECTRICAL REQUIREMENT:

Range hood is supplied with 10amp cord & plug.

OPTIONAL ACCESSORIES

RECIRCULATING ACCESSORIES

Carbon filter Code: CF110 (requires x2)

** Please NOTE this still needs to be vented through cupboards **

RANGEHOOD VENTILATION KITS

RHKE65 – Wall – Eave vent kit

RHKMR65 – Universal metal roof kit, includes flashing

RHKTR65 – Universal tile roof kit, includes flashing

