

# caroma®


## Trident

Vitreous China Concealed Trap Pan

CI/SfB	(74.1)	g3
Date	July 2008	

Supersedes all previous issues

# 4.06.1





Shown with Sovereign 2000 Cistern

A distinctive 4.5 litre vitreous china toilet pan featuring rounded contours with a concealed trap for easy cleaning. The **Trident Smartflush** pan can be coupled with the range of Caroma exposed and concealed cisterns for optimum matched suite performance. Suitable for general purpose applications.

- Pan:** **Trident Smartflush** 4.5 litre full flush wash down pans with open flushing rim.
- Traps:** S or P-trap unvented only.
- Inlet:** 50mm Back inlet for concealed cisterns and flushvalve options.
- Cisterns:**
  - Vitreous China Cisterns**  
Standard **Sovereign 2000 Cistern** – has a free fitting lid and is suitable for domestic and light commercial applications. Fitted with a Quietflow 2 inlet valve. Also suitable for **Profile**, **Regal II** and **Regal** cisterns.
  - Plastic Concealed Cisterns**  
Several Caroma concealed cistern options are available – **Compact Under Counter** dual flush cistern, **Invisi inwall/induct** cisterns.
  - Plastic Exposed Cisterns**  
**Trident Smartflush**, **Cosmo Smartflush**, **Slimline** and **Verona Aire** cisterns.
- Fixing:** The cistern is secured directly to the finished wall with simple alignment adjustment provided.
- Seats:** The following Caroma seats are recommended: **Caravelle 2000**, **Avalon** or **Trident**. See sheet 5.01 SEATS for further details.
- Colours:** White and Ivory.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Top view dimensions: 364 (width), 168 (cistern height), 425 (total height), 635 min. / 725 max. (overall height), 152 (seat width), 350 (pan width).

Side view dimensions: 300 (width), 196 (inlet/overflow height), 865 (low level approx. height), 785 (ultra low level approx. height), 395 (total height), 110 (pan depth), 165 (recommended setout), 165 min. (setout with Trident seat).

Front view dimensions: 300 (width), 196 (inlet/overflow height), 865 (low level approx. height), 785 (ultra low level approx. height), 395 (total height), 110 (pan depth), 165 (recommended setout), 165 min. (setout with Trident seat).

Trident Pans:	Code No.
4.5/3 litre	S trap 606400
	P trap 606450

	A	B	C
Low level	940 approx.	590	490
Ultra low level	860 approx.	510	410

**Note:** All height dimensions to underside of pan, make allowance for bedding.

**Bedding:** The pan should be fixed to the floor with a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast drying cement in the bedding mixture. When bedded the back of the foot of the pan should be approximately 10mm above the finished floor.

**Screw fixing:** The pan should be bedded with an acetic cured silicone sealant and fixed with corrosion resistant screws and pan guard washers. Use Caroma screw fixing kit. Code No.601150.