Caroma

Torres Urinal

Vitreous China Wall-Hung Urinal

CI/SfB |(74.4) | g3 | Date December 2014

Supersedes all previous issues

7.04.2



Caroma Torres Urinal



A general application wall hung urinal with integral trap. An adjustable spreader is suitable for installations with increased cistern head height. The spreader channels water to the front and back areas providing a wash down of the bowl on each flush.

Available with top inlet Code No.666101W and back inlet Code No.666102W and with a stainless steel grate as standard.

Inlet: Standard options include top inlet for exposed sparge pipe with compression

fitting, or back inlet for concealed pipes with 20mm O.D. inlet for connection with

capillary or compression fittings.

Outlet: Two rubber connection seals are supplied for a push-on fit with 50mm O.D. brass

tube and 50mm DWV plastic pipe.

Flush Action: An important feature is the chrome plated adjustable spreader which allows

cisterns to be installed at increased head height.

Cisterns: Vitreous china urinal pull chain cistern. Refer sheet 6.02.1

Slimline urinal pull cord cistern. Refer sheet 6.05.3

Caroma concealed cistern options available – **Invisi** 1.8 litre Inwall/Induct/Inceiling for 1 stall 3 star installation, conversion to 4 litre max for 2 stall 1 star installation or 6 litre max for 3 stall 0 star installation. For button options see Section 6. **Invisi**

II Inwall/Induct/Inceiling (available November 2008), see Section 6.

Fixing: The Torres urinal is fixed to the wall with – D.232 Concealed support bracket;

cast aluminium natural finish supplied with cadmium plated locating bolts and fasteners. Back Inlet or Top Inlet installations Fixing packs available includes D.232 Concealed support bracket, sparge pipe bracket and spreader. Also suitable for installation with the **D.780 Sanifix** bracket code No. 687780 and

Urinal All thread fixing pack Code No. 687810.

Colours: White only.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing

variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications

without notice.

