## Caroma®

CI/SfB | (74.2) | g3 | Date March 2017

Supersedes all previous issues

2.60.2

## Luna

Vitreous China Semi Recessed Vanity Basin (without tap landing)

Nominal Size: 450mm x 320mm





## Vitreous China Semi Recessed Vanity Basin (without tap landing)

Basin Size: 450mm x 320mm (nominal)



Tapware shown not included.

Classic and relaxed. The subtle, subdued curves of **Luna** basins will effortlessly flow into any contemporary bathroom design. This basin is suitable for domestic and commercial applications.

**Tap Holes:** Basin available in: No tapholes Code No.873500.

Waste Outlet: The basin has been designed for the Caroma Chrome Flush Fitting Waste

(supplied) which is suitable for a 40mm trap connection.

Alternative waste options are available — Chrome Waste Code No. 687328C, Vandal Resistant Flush Fitting Chrome Waste Code No.687141, Covered Chrome Plug and Waste Code No.687142, Vandal Resistant Covered Chrome Plug and Waste Code No.687143 and Chrome Pop-Up Plug and Waste 687329C.

Bowl Capacity: 7 litres

**Overflow:** Overflow not available.

**Fixing:** D.250 Bracket with Tie Hooks – Supplied. Recommended for domestic and

general commercial use. Two D.250 brackets are fixed to the underside of the counter top to secure the tie hooks which anchor the back of the basin to the

counter.

The basins must be sealed to the top and front section of the counter with an acetic cured silicone sealant. **Epoxy type glues must not be used.** 

The basin is supplied with a template which must be used for the counter top

cut-out.

**Important:** For granite or marble tops, fix two 20mm thick wooden blocks in the bracket position on the underside of the granite/marble with fast setting two part epoxy. When fully set screw the brackets into position on the wooden blocks.

Other suitable fastening systems may be used.

Colours: White only.

**Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing

variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications

without notice.

