# **PVC NON PRESSURE SYSTEM**

## **STORMWATER**



#### W160100KA • DN100 Stormwater PVC-U Kerb Adaptor SWJ

**APPLICATION** Connects pipeline conveying rainwater or surface water to a discharge point in a section of kerb and channel.

#### **FEATURES**

- Australian Made
- BEP PVC Manufactured from Best Environmental Practice PVC
- Installation Economics

- Operation Efficiencies
- · Corrosion Resistant
- Tree root intrusion resistance

# TECHNICAL DATA PRODUCT PROPERTIES

Primary Material	PVC
Colour	White
Joint Type	SWJ
Allowable Operation Temperature - Degrees	50
Average # of Joints per Litre – Iplex Solvent	40
Average Number of Joints per Litre - Iplex Primer	120
Unprotected UV Exposure (years)	2 Years

#### **PRODUCT DIMENSIONS**

Rating	SN2
UOM	EA
Nominal	100mm
ID	100mm
Wall Thickness	2.0mm
Weight	0.3kg
Carton Qty	15
Carton Weight (kg)	4.5kg

## **ENVIRONMENTAL CREDENTIALS AND STANDARDS**

Environmental Accreditation	Best Environmental PVC - PVC Certificate No. BEP-PVC 0037

AS/NZS 1254 "PVC-U Pipes and Fittings for Stormwater and Surface Water Applications"

# **MATERIAL PROPERTIES**

**Product Standard** 

#### **MECHANICAL**

Density Specific Gravity	1.47
Ultimate Tensile Strength	52MPa
Yield Strain	5.5%
Compressive Strength	66MPa
Tensile Modulus	2750MPa
Hardness Shore D	85
Poissons Ratio	0.38
Ring Bending Modulus (3mins)	3200MPa
Ring Bending Modulus (50Yrs)	1400MPa

### **THERMAL**

Coefficient of Thermal Expansion	7 x 10⁻⁵/°C
Thermal Conductivity	0.138W/m.K
Specific Heat	1047 J/kg/°C
Vicat Softening Temperature	75°C
Flammability	Will not support combustion
Fire Index – Ignitability	8
Fire Index – Smoke Development	8
Fire Index – Spread of Flame	0
Fire Index – Heat Evolved	1

© Copyright: Iplex Pty Ltd 2019 all rights reserved. All drawings and information contained thereon are the exclusive property of Iplex Pipelines. Unless specifically noted, this drawing and information enclosed are subject to change at any time. Measures are for reference purpose only. If critical please contact Iplex Pipelines.



