

**NOTE**  
Check the rubber seal under each spindle.

**HOT**  
← RED

**COLD**  
← BLUE

**EXPLODED VIEW**

**BREACH SET-UP**

Ensure the seats in the Breach are in good condition and are free of foreign objects.

**ADJUSTMENT**  
0-12mm Standard  
13-24mm Extended

Front Wall Surface

Breach

**1**

Firmly screw Cartridge into the Breach.

**DO NOT OVERTIGHTEN**

**2**

Fit Fibre Washer around the Cartridge, then firmly fasten the Bonnet onto the Cartridge using a Tube Spanner.

**3**

Push the Dress Plate onto the Bonnet.

**4**

Place the Handle Screw and Splined Cap onto the Cartridge Shaft, then insert the Screw into the Cartridge Shaft, fastening tightly.

**5**

**NOTE**  
OFF ← H → ON  
OFF ← C → ON

Push Handle onto the spline, then fasten Locking Nut to Handle, rotating counter clockwise using spanner.

recommended working pressure  
**150-500KPa**  
maximum hot water temperature  
**75 degrees**

**NOTE:**

- If the pressure exceeds or is likely to exceed 550kpa, an approved pressure limiting device must be installed.
- Flush out all pipe work prior to installation.
- If the water temperature exceeds 75°C, an approved tempering valve must be fitted.
- Installation should comply with Australian standard AS3500.1 or relevant local authority requirements.
- Showers may not be suitable for use within:
  - Gravity-fed water systems

- Some instantaneous hot water systems; or
- Pressure supply less than 150kPa;

**NOTE:** The 500kPa maximum water supply pressure does not apply to fire service outlets.

Failure to comply with the above may void all warranties.

**WARRANTY:**  
Please refer to the full warranty statement enclosed with the product before installing.

**MAINTENANCE AND CARE:**

- Chrome plated surfaces should be cleaned with mild liquid detergent or soap and water.
- Do not use cream cleaners or citrus based cleaning products, as they are abrasive.
- Use of unsuitable cleaning agents may damage the surface. Any damage caused in this way will not be covered by warranty.

**DISCLAIMER:**  
While we aim to ensure the specifications shown are correct at the time of printing, we reserve the right to make modifications without prior notice. Always use the physical product measurements for mark-ups and roughing-in as the line drawing shown may differ from the actual product over time.

\*All measurements are shown in millimeters.