



1

Position Mounting Rail in preferred location. Ensure Rail is level and mark positions of holes.

2

For fixing to brick walls with hard plaster or ceramic tiled surface:
 Using a 6mm masonry drill bit, drill holes 30mm deep. Press plugs into holes. Guide Self Tapping Screws through the Mounting Rail, into the plastic plugs and tighten with screwdriver.

For fitting to stud walls clad with wallboard, with or without ceramic tiles:
 Using a 10mm drill bit, drill through to wall cavity. Remove Screws from Spring Toggles. Guide Screws through the Mounting Rail, screw on the Spring Toggles and push them into the holes. Tighten with screwdriver.

3

Push Rail onto Mounting Rail as shown

4

Fasten 2 X M4 Cap Screws firmly to Secure Rail to Mounting Rail as shown

5 Apply TEFLON tape to Wall Outlet Tail. Screw Wall Adaptor firmly against wall surface. Screw end of Hose into Wall Outlet. Push on Wall Outlet with Hose onto Wall Adaptor and Fasten Grub Screw.

Wall Outlet Tail
 Wall Adaptor
 Wall Outlet
 Grub Screw

Insert Rubber Washer and Flow Restrictor as shown into Shower Hose Cone. Screw Shower Hose Cone to Hand Shower.

Flow Restrictor
 Rubber Washer

Test and check for leaks

recommended working pressure
150-500KPa
 maximum hot water temperature
75 degrees

NOTE:
 - If the pressure exceeds or is likely to exceed 550kpa, an approved pressure limiting device must be installed.
 - Flush out all pipe work prior to installation.
 - If the water temperature exceeds 75°C, an approved tempering valve must be fitted.
 - Installation should comply with Australian standard AS3500.1 or relevant local authority requirements. Showers may not be suitable for use within:
 • Gravity-fed water systems

• Some instantaneous hot water systems; or
 • Pressure supply less than 150kPa;
 NOTE: The 500kPa maximum water supply pressure does not apply to fire service outlets.

Failure to comply with the above may void all warranties.

WARRANTY:
 Please refer to the full warranty statement enclosed with the product before installing.

MAINTENANCE AND CARE:
 - Chrome plated surfaces should be cleaned with mild liquid detergent or soap and water.
 - Do not use cream cleaners or citrus based cleaning products, as they are abrasive.
 - Use of unsuitable cleaning agents may damage the surface. Any damage caused in this way will not be covered by warranty.

DISCLAIMER:
 While we aim to ensure the specifications shown are correct at the time of printing, we reserve the right to make modifications without prior notice. Always use the physical product measurements for mark-ups and roughing-in as the line drawing shown may differ from the actual product over time.

*All measurements are shown in millimeters.