



1 Drill 4 x 6mm holes 32mm deep as indicated in diagram.

900mm
35mm
35mm

2 Insert Plastic plugs into holes. Position Mounting Flanges over holes. Insert screws into plugs and tighten firmly

slots to be vertical for adjustment.

3 Apply Teflon Tape to threaded tail. Screw wall outlet connector onto threaded tail. Tighten firmly.

Threaded Tail
Wall Outlet Connector

4

a) Slide Shower Riser onto Rail.
b) Attach Upper and lower Pillars onto Rail. Fasten lower Pillar in place with grub screw. Note: Ensure Rail locating hole is facing grub screw.

Upper Pillar
Riser
Rail
Grub Screw
Lower Pillar

5

Place Dress Rings over Mounting flanges. Push Rail Assembly onto Mounting Flanges. Tighten Grub Screws firmly.

Rail Assembly
Mounting Flange x 2
Dress Ring x 2
Grub Screw x 2

6

a) Ensure rubber washers are inserted into hose and check valve is inserted into hand shower.
b) Carefully connect hose to wall outlet connector.
c) Connect hand shower to hose.

Wall Outlet Connector
Hand Shower
Check Valve
Mesh Washer
PCW
Rubber Washer
Hose

recommended working pressure
150-500KPa
maximum hot water temperature
75 degrees

NOTE:

- If the pressure exceeds or is likely to exceed 550kpa, an approved pressure limiting device must be installed.
- Flush out all pipe work prior to installation.
- If the water temperature exceeds 75°C, an approved tempering valve must be fitted.
- Installation should comply with Australian standard AS3500.1 or relevant local authority requirements.
- Showers may not be suitable for use within:
 - Gravity-fed water systems

- Some instantaneous hot water systems; or
- Pressure supply less than 150kPa;

NOTE: The 500kPa maximum water supply pressure does not apply to fire service outlets.

Failure to comply with the above may void all warranties.

WARRANTY:
Please refer to the full warranty statement enclosed with the product before installing.

MAINTENANCE AND CARE:

- Chrome plated surfaces should be cleaned with mild liquid detergent or soap and water.
- Do not use cream cleaners or citrus based cleaning products, as they are abrasive.
- Use of unsuitable cleaning agents may damage the surface. Any damage caused in this way will not be covered by warranty.

DISCLAIMER:
While we aim to ensure the specifications shown are correct at the time of printing, we reserve the right to make modifications without prior notice. Always use the physical product measurements for mark-ups and roughing-in as the line drawing shown may differ from the actual product over time.

*All measurements are shown in millimeters.