



GENERAL INFO

SEDIMENT REMOVAL CARTRIDGE

Pleated Polyester Washable Cartridges

The Puretec PP Series sediment cartridges use pleated media to maximise dirt holding capacity and extend the time period between changes or cleaning. It removes dirt, rust, sediment and particulate matter from your water.

The Puretec PP Series sediment cartridges are resistant to both bacteria and chemical attack, making them suitable for a variety of residential, commercial and industrial applications.

FEATURES & BENEFITS

- Washable
- Available in 1, 5, 10, 20 and 50 microns
- Length options - 10", 20", 30" and 40"
- Pleated design maximises dirt-holding capacity.
- Ideal for pre-filtration in high sediment applications.
- Temperature ratings up to 60°C.
- Flow rates up to 200 litres/minute.

MATERIALS OF CONSTRUCTION

- Filter Media Polyester Fabric
- End Caps Polyurethane
- Core Polypropylene
- Temperature Rating (4.4°C to 60°C)

CARTRIDGE SPECIFICATIONS

Size	Ordering Code	Micron Rating*	Size	Description	Flow (Lpm)
10"	PP011	1	Standard 2.5" X 10"	cyst reduction	40
	PP051	5	Standard 2.5" X 10"		41
	PP101	10	Standard 2.5" X 10"		42
	PP201	20	Standard 2.5" X 10"		43
	PP501	50	Standard 2.5" X 10"		46
20"	PP012	1	Standard 2.5" X 20"	cyst reduction	80
	PP052	5	Standard 2.5" X 20"		82
	PP202	20	Standard 2.5" X 20"		86
	PP502	50	Standard 2.5" X 20"		92
10" LD	PP01LD1	1	Large diameter 4.5" X 10"	cyst reduction	88
	PP05LD1	5	Large diameter 4.5" X 10"		90
	PP10LD1	10	Large diameter 4.5" X 10"		92
	PP20LD1	20	Large diameter 4.5" X 10"		94
	PP50LD1	50	Large diameter 4.5" X 10"		100
20" LD	PP01LD2	1	Large diameter 4.5" X 20"	cyst reduction	175
	PP05LD2	5	Large diameter 4.5" X 20"		180
	PP10LD2	10	Large diameter 4.5" X 20"		183
	PP20LD2	20	Large diameter 4.5" X 20"		188
	PP50LD2	50	Large diameter 4.5" X 20"		200

*Micron rating is nominal. Protect from freezing.