

ActivFlo



Technical Datasheet



The ActivFlo by RBM domestic range of water conditioners offer maximum protection for fluid systems and their components against the buildup of limescale. Featuring ActivFlo's unique patented alloy coil, the unit uses a catalytic method of water treatment to change the calcium and bicarbonate ions to precipitate from the water forming an insoluble microscopic calcium carbonate crystal called aragonite, the smooth surface of this crystal cannot adhere to surfaces.

Features and Benefits:

No power supply required

Life expectancy in excess of 20 years

Suitable for whole house protection

Helps to improve the efficiency of heating systems

Fit and forget installation

Stainless steel housing

*15 year product warranty



Watermark approved for safe drinking water application

RBM Systems Pty Ltd
PO Box 4104, Gumdale
QLD 4154, Australia

T: +61 7 3073 2428 M: +61 435 217 237
rbmsystems.com.au

Maximum Operating Pressure 16 Bar
 Maximum Operating Temperature 99°C
 Inlet Connection Size Compression Fittings

Item Code	Model
RBM-AF0015C	15mm ActivFlo Water Conditioner Compression Connection
RBM-AF0020C	20mm ActivFlo Water Conditioner Compression Connection
RBM-AF0025C	25mm ActivFlo Water Conditioner Compression Connection



Item Code	Overall Length	Connection
RBM-AF0015C	158 mm	15mm Copper olive & Brass nut compression
RBM-AF0020C	200 mm	20mm Copper olive & Brass nut compression
RBM-AF0025C	305 mm	25mm Copper olive & Brass nut compression