



Standard Camera Reel with TruSense™



For a FREE DEMONSTRATION*
contact your RIDGID representative
*Selected products only & subject to availability & location

Equipped with the largest diameter SeeSnake® camera head, the Standard is your go-to machine for inspecting long runs in main sewer laterals. Everything about the Standard suggests durability, from the all-metal frame and hardened stainless steel camera head to the stiff cable. Newly available TruSense technology provides a high dynamic range (HDR) image sensor and a TiltSense™ inclinometer for SeeSnake CSx series Wi-Fi enabled monitors.

- First data enabled camera heads designed for drain inspection
- HDR image sensor offers bright, clear in-pipe imaging in difficult lighting conditions
- TiltSense data sensor displays the camera's pitch on CSx series Wi-Fi enabled monitors
- Self-leveling option ensures camera image is always upright
- Download the free HQx Live app to view and record video from a CSx series monitor on your phone or tablet



RIDGID.COM.AU



CONNECT WITH US

- ridgid australia
- RIDGID Tools
- ridgid_australia



SPECIFICATIONS

- Camera Head..... 35mm TruSense™ fixed or self-leveling
- Light Source..... High-Intensity LED
- Push Cable Length..... 200' (61m)/325' (99m)
- Push Cable Diameter..... 0.44" (11.2mm)
- Push Cable Minimum Bend Radius..... 4.5" (114 mm)
- Line Capacity..... 2' to 12' (51mm to 305mm)
- 512Hz Sonde..... High-power Flexmitter
- Dimensions (LxWxH)..... 25" x 14" x 17" (635 x 356 x 432mm)
- Operating Temperature..... 14°F to 122°F (-10°C to 50°C)
- Storage Temperature..... 14°F to 158°F (-10°C to 70°C)
- Ingress Protection (without Monitor)..... IPx5

ORDER INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT (lb.) (kg.)	
63583	325' Standard 35mm SL TruSense	54	24
63603	200' Standard 35mm SL TruSense	42	19

ACCESSORIES

CATALOG NO.	DESCRIPTION
64497	75mm Star Guide, 35mm Camera, Pkg of 20
97852	85mm Pipe Guide, 35mm Camera, Pkg of 10
64502	150mm Pipe Guide, 35mm Camera, Pkg of 10
93387	Guide Hoop, 35mm Camera, Pkg of 4
97832	75mm Roller Dolly, up to 6" Pipe
17563	Spanner Wrench, 35mm



High Dynamic Range (HDR) image sensor offers clear in-pipe imaging.

REPLACEMENT PARTS

CATALOG NO.	DESCRIPTION
35108	325' SeeSnake Standard Push Cable Assembly
35103	200' SeeSnake Standard Push Cable Assembly
64627	Interconnect Cable, 33' SeeSnake Standard



TiltSense™

Data sensor displays cameras in-pipe pitch.



RIDGID.COM/seesnake

Ridge Tool (Australia) Pty Ltd ABN 96 008 446 482 • 127 Metrolink Circuit Campbellfield Victoria 3061
 Phone 1800 743 443 Fax 1800 801 976 Email ridgid.australia@emerson.com Web www.ridgid.com.au

All sales subject to Ridge Tool Company Terms and Conditions of Sales.

999-997-271.10
 Effective Date: January 13, 2023