



Quick Reference Guide

Brief Product Specs

Multijet Meter

20-40mm Pulse Capable 1P/10L

The meter is roller protected turbine suited for internal and external use.

Must be installed in horizontal position only.

AS3565.1/AS3565.3 & NMI 14/3/1



Positive Displacement Meter



Pulse Capable 1P/5L

Can be installed in horizontal or vertical position.
AS3565 & NMI 14/3/1

Hot Water Meter

Pulse Fitted 1P/10L

Hot water temp 90°C Working Pressure 1600kPa Fitted with reed switch and couplings.



Helix Meters

50-200mm Pulse Capable 1P/10L

High accuracy from low flows to high flows.

Max working pressure 1600kPa Water temp 60°C



Sub Metering Kits

20 and 25mm.

Available in different configurations. Meter Thread, STD copper connection NSW Thread, STD copper connection

Also available in SharkBite copper and PEX connections.

Tapping Kits

Rapid tap is for 20-25mm tapping. For pressure and dry taps.

Major tap is for 32-50mm.

Watgas for 150 Tapping.

Ball Valves

Water Marked to AS34796 and AS5200.

Long handle, straight or short handle. Forged DR bottom loading. Lockable multiple positions. Right angle 90°

As above.

Tapping Bands

Standards marked.

AC/DI & PVC Pipe

3/4 - 2" BSP outlet



RMC Metering product range:

- Multijet Water Meters
- Bullet Positive Displacement Meters
- Industrial Cold Water Meters
- Harvest Irrigation Meters
- Logging/Monitoring?GSM Products
- Water meter Accessories
- Isolating Valves
- Hot Water Meters



Water Meter Installation Guide

Multijet Hot & Cold Meter

Horizontal installation only

Dial facing up

Positive Displacement Meter

Horizontal and vertical installation

Dial can be in any direction


Helix 50-200

Horizontal installation only

Dial facing up

Single Jet Hot Water Meter

Vertical installation only



Standards Approved

Reliance Worldwide Corporation (Aust.) Pty. Ltd. supplies a range of water meters suitable for both hot and cold water and for domestic, commercial and industrial applications. Our meters conform to Australian standards and are available in configurations suitable for each state in Australia. We also supply water meters that conform to selected international standards. A range of automatic reading products and logging/monitory products are available to complement our water meter products.

Want more information?

Call our national customer service hotline 1800 810 803 or visit www.rmc.com.au





Download a QR code reader on your smartphone and scan this to go to the RMC website.



Water Meters - Cold 20mm - 200mm **Multijet & Positive Displacement**







WM201PD	20mm	DC	NSW Thread
WM202PD	20mm	DC	Meter Thread
WM203PD	20mm	DC	BSP Thread
WM251PD	25mm	DC	NSW Thread
WM252PD	25mm	DC	Meter Thread
WM253PD	25mm	DC	BSP Thread

Hot Water Meter



WM151HWM	15mm	BSP Thread
WM201HWM	20mm	BSP Thread
WM251HWM	25mm	BSP Thread
WM301HWM	32mm	BSP Thread
WM401HWM	40mm	BSP Thread
WM501HWM	50mm	BSP Thread

Industrial Meters



Aust Length



Meter Connectors



Octave Ultra Sonic Meter

WM5000CT	50mm	Flange
WM8000CT	80mm	Flange
WM10000CT	100mm	Flange
WM15000CT	150mm	Flange
WM20000CT	200mm	Flange



Reed Switches

WM598	Multijet	20-40mm
WMRS5	Positive Displacement	20-25mm
WMSP011	Arad 50mm	1P per 10L
WMSP012	Arad 80mm	1P per 10L
WMSP013	Arad 100mm	1P per 10L
WMSP014	Arad 65mm	1P per 10L
WMSP004	Arad 150mm	1P per 100L
WMSP005	Arad 200mm	1P per 100L

Meter Kits



Ball Valves

Straight Lockable



90° Lockable



Flange Connection Kits

	J		
IN148	32mm	Oval	
IN149	40mm	Oval	
IN154	50mm	Round	
IN155	80mm	Round	
IN156	100mm	Round	

Tapping Bands





12151	100 x 20
12152	100 x 25
12153	100 x 32
12154	100 x 40
12155	100 x 50
12171	150 x 20
12172	150 x 25
12173	150 x 32
12174	150 x 40
12175	150 x 50

PVC Pipe Full Circle*

12041	100 x 20
12042	100 x 25
12061	150 x 20
12062	150 x 25

*For further sizes please contact Customer Care on 1800 810 803

Tapping Kits



