

APPLICATIONS



8





PRODUCT REFERENCE: SA91

Sanicondens® Best Flat

The Sanicondens® Best Flat is specifically designed for disposal of condensate from air conditioning units, refrigeration units and is ideal for ice machines due to its low profile design.



WHY CHOOSE THIS PRODUCT?

3.5 L tank

Three entry points

Working temperature of 35°C

Will handle temperatures up to 80°C for short periods (5 minutes)


Supplied with 1.5 m power cable and 5m of discharge pipe

High level alarm connectivity

Low profile inlet connection

TECHNICAL CHARACTERISTICS

Noise Level	45 dB		
Motor Power	60 Watts		
Flow Rate	342 L/h		
Voltages	220-240 V/50 Hz		
Tank Volume	3.5 L		
Working Waste Water Temp	35°C/Max 80°C (intermittent)		
Product Weight	2 kg		
Overall Measurements	401 x 170 x 138 mm		
Inlet Pipework	25/32 mm		
IP Rating	IP20		



VERTICAL/HORIZONTAL PERFORMANCE

4.5m	max 15m
4m	max 20m
↑ 3m	max 30m
↑ 2m	max 40m
1m	max 50m
	1%

FLOW RATE PERFORMANCE CHART

		~		141 1741						
Disch	arge he	ight (m)								
5										
4										
3										
2										
1										
_ ا										
	1	2	3	4	5	6	7			
OUTPUT (litres/min)										



Made in France to the highest standards, needs to be installed by a licensed plumber