

AUSTRALIAN MADE AND OWNED




SharkBite® fittings and pipe are manufactured in Australia by Reliance Worldwide Corporation (Aust.) Pty. Ltd. in state of the art facilities. Stringent quality control and advanced manufacturing procedures guarantee product satisfaction.

25 YEAR WARRANTY¹



The SharkBite® range of fittings and PEX pipe can be relied upon to perform year after year. SharkBite® is backed by the Reliance Worldwide Corporation (Aust.) Pty. Ltd. 25 year warranty.

VERSATILE AND REUSABLE



Can be easily disconnected using the SharkBite® Disassembly Clip or Tongs. Fittings can be rotated once installed, allowing for a more versatile, easier use, especially in confined spaces. This feature is particularly useful where repairs and or maintenance are required.

QUICK AND EASY



SharkBite® is quick and easy to install, making it the most time effective plumbing system available, allowing the installer to move onto the next job faster than ever before.

Utilising state of the art push-to-connect design, DR brass fittings, the SharkBite® system is easily assembled by hand.

STANDARDS APPROVED



SharkBite® fittings and PEX pipe comply with and are approved to Australian Standards AS 2537 and AS 2492 – 1994 respectively.

SHARKBITE®

PLUMBING SYSTEM



SharkBite® has established a reputation as the world's #1 push-to-connect plumbing system.

- Quick and easy to use
- Fittings for PEX and Copper Pipe
- Conversion Fittings to other pipe systems
- Assemble by hand, no costly tools
- For use on hot and cold water
- Approved for behind walls and in ground
- Can be disconnected and reconnected
- Australian made and owned
- 25 year warranty¹
- For a copy of the Technical Manual, refer to the SharkBite® website

¹ See sharkbite.com.au for further information on SharkBite® warranty.

Contents of this brochure are subject to change, please visit our website for most up-to-date product information.

NOTHING BEATS THE SHARK



SharkBite®

☎ 1800 810 803 ✉ sales@rmc.com.au
🌐 sharkbite.com.au 📱 /SharkBiteAustralia
🐦 @SharkBiteAus 📷 @SharkBiteAus

27-28 Chapman Place
Eagle Farm QLD 4009, Australia



SharkBite® is a division of Reliance Worldwide Corporation (Aust.) Pty. Ltd. | ABN 71 004 784 301 | © July 2019

**CUT.
PUSH.
DONE.**

sharkbite.com.au

STARTER PACK



F4001 Starter Pack (fittings sold separately)

Whether you're a fresh faced apprentice or an experienced tradie looking to start your SharkBite® collection, the SharkBite® Starter Pack provides the essentials to get your job underway.

The F4001 Starter Pack is a basic kit that includes the essential tools and accessories used for joining Copper Tube and PEX Pipe. The SharkBite® Starter Pack comes housed in a sturdy Exactapak, which includes multiple stock-wells, so that as you build up your SharkBite® fittings over time, you'll always have a place to store them neatly, keep them clean and free from contamination.

This pack is also perfect for a new apprentice who may already have access to SharkBite® plumbing fittings but requires their own installation tools.

Starter Pack Includes:

- Tube Cutter 16mm to 25mm PEX
- Copper Depth Gauge and Deburrer
- 4 x Disassembly Tongs (16mm PEX, 20mm PEX, DN15 Cu & DN20 Cu)
- 6 x Disassembly Clips (2 x 16mm PEX, 1 x 20mm PEX, 2 x DN15 Cu & 1 x DN20 Cu)
- Hard Case Exactapak



PEX FITTINGS



- Used to connect SharkBite® PEX Pipe
- PEX fittings have mustard coloured ends
- Fittings are rotatable after connection
- Fittings can be installed on wet pipe even with water flowing
- Fittings can be disconnected and reconnected as required

INSTALLATION OF PEX PIPE

Safe Seal Indicator Marks




Cut

Using SharkBite® PEX Pipe Cutters, cut the pipe squarely between two of the SharkBite® safe seal indicator marks as shown in the picture. Ensure pipe is round, clean and free of debris.




Push

Insert the pipe through the release collar to rest against the grab ring. Push the pipe firmly with a twisting action and push to the SharkBite® safe seal indicator mark.



Done

Ensure the SharkBite® safe seal indicator mark aligns with the release collar as shown.



Disassembly

Using the Disassembly Tongs or Clip, fittings can be easily changed, removed and the fittings reused.

INSTALLATION PER AS 3500

COPPER FITTINGS




- Used to connect copper systems
- Copper fittings have black coloured ends
- A range of fittings and adapters are available

INSTALLATION OF COPPER PIPE




Cut

Using a pipe cutter, cut the copper tube to length making sure the pipe is cut squarely. Ensure pipe is round, clean and free of debris.



Deburr

Remove burrs from the pipe using the SharkBite® deburrer and depth gauge.



Mark

Mark the pipe with a marker using the depth gauge.




Push

Insert the pipe by pushing firmly until a positive click is heard.



Done

Ensure the mark made with depth gauge aligns with the release collar.




Disassembly

Using the Disassembly Tongs or Clip, fittings can be easily changed, removed and the fittings reused.

INSTALLATION PER AS 3500

PEX FITTINGS

SHARKBITE® 25mm OD PEX CONNECTIONS CAN BE USED FOR PEX OR COPPER (DN25CU)






								
F1 Straight Coupling F008 16mm OD x 16mm OD F016 20mm OD x 20mm OD F020 25mm OD (DN25Cu) x 25mm OD (DN25Cu)	F1R Reducing Coupling F058 20mm OD x 16mm OD F060 25mm OD (DN25Cu) x 20mm OD	F2 Straight Female Connector F072 16mm OD x 15Fl F068 16mm OD x 20Fl F088 20mm OD x 20Fl F094 25mm OD* x 25Fl	F3 Straight Male Connector F120 16mm OD x 15ML F116 16mm OD x 20ML F138 20mm OD x 15ML F134 20mm OD x 20ML F142 25mm OD (DN25Cu) x 20ML F140 25mm OD (DN25Cu) x 25ML	F12 Elbow F248 16mm OD x 16mm OD F256 20mm OD x 20mm OD F260 25mm OD (DN25Cu) x 25mm OD (DN25Cu)	F13 Male Elbow F280 16mm OD x 15ML	F14 Female Elbow F308 16mm OD x 15Fl	F15BP Backplate Female Elbow F334 16mm OD x 15Fl F340 20mm OD x 20Fl	F19BP Backplate Male Elbow F350 16mm OD x 15ML x 75mm F351 16mm OD x 15ML x 185mm F352 16mm OD x 15ML x 100mm F354 20mm OD x 20ML x 185mm F356 20mm OD x 15ML x 100mm F358 20mm OD x 15ML x 200mm
								
Top-Plated Male Elbow F336 16mm OD x 15ML x 100mm F336-230 16mm OD x 15ML x 230mm	Recycled BP's F339-90 20mm SB x 5/8" BSP x 90mm F339-200 20mm SB x 5/8" BSP x 200mm	F24 Equal Tee F362 16mm OD x 16mm OD x 16mm OD F370 20mm OD x 20mm OD x 20mm OD F374 25mm OD (DN25Cu) x 25mm OD (DN25Cu)	F25, F26, F27 Unequal Tee F412 20mm OD x 20mm OD x 16mm OD F416 25mm OD (DN25Cu) x 25mm OD (DN25Cu) x 20mm OD F444 20mm OD x 16mm OD x 20mm OD F454 20mm OD x 16mm OD x 16mm OD	F61 Stop End F514 16mm OD F518 20mm OD F520 25mm OD (DN25Cu)	F62 Straight Tap Connector F526 16mm OD x 15Fl Nut F530 20mm OD x 20Fl Nut	F63 Bent Tap Connector F532 16mm OD x 15Fl F536 20mm OD x 20Fl	PEX Tail Reducer F720 16mm OD Tail x 20 OD F722 16mm OD Tail x 25 OD F724 20mm OD Tail x 25 OD	PEX Tail / Capillary Tail F608 16mm OD Tail x 15 Cap Tail F609 20mm OD Tail x 20 Cap Tail
								
PEX Tail / Copper Adaptor F600 16mm OD Tail x 15 Cu F602 16mm OD Tail x 20 Cu F604 20mm OD Tail x 15 Cu F606 20mm OD Tail x 20 Cu	PEX Flare Adaptor F610 16mm OD x 15 Flare F612 20mm OD x 20 Flare	Ball Valves BVF670 16mm OD x 16mm OD BVF672 20mm OD x 20mm OD BVF674 25mm OD (DN25Cu) x 25mm OD (DN25Cu) BVF680 16mm OD x 15Fl BVF682 20mm OD x 20Fl BVF684 25mm OD x 25Fl (DN25Cu)	Recessed Right Angled Breech F630 300mm F632 200mm	Recessed - Straight Breech F642 200mm (While stocks last)	Shower Right Angled Breech F650 200mm F652 150mm	Shower Right Angled Breech F655 200mm Inverted F657 150mm Inverted	Shower/Bath Right Angled Breech F662 300mm	Manifolds F690-3T 20mm OD x 3 Way 16mm PEX Take Offs x 20mm OD F690-4T 20mm OD x 4 Way 16mm PEX Take Offs x 20mm OD

COPPER FITTINGS

SHARKBITE® 25mm OD PEX CONNECTIONS CAN BE USED FOR PEX OR COPPER (DN25CU)

							
No1 Straight Coupling RA008 DN15 RA016 DN20	No1R Reducing Coupling RA058 DN20 x DN15 F061 DN25 (25mm OD) x DN20	No2 Female Connector RA072 DN15 x 15mm Fl RA088 DN20 x 20mm Fl	No3 Male Connector RA120 DN15 x 15mm ML RA134 DN20 x 20mm ML	Hot Water Elbow RA380 DN15 x 20mm ML	No12 Elbow RA248 DN15 RA256 DN20	No15BP Female Lugged Elbow RA334 DN15 x 15mm Fl RA340 DN20 x 20mm Fl	No19BP Male Lugged Elbow RA350 DN15 x 15mm ML 75mm RA351 DN15 x 15mm ML 185mm RA352 DN15 x 15mm ML 100mm
							
No24 Equal Tee RA362 DN15 RA370 DN20	No25 Unequal Tee RA412 DN20 x DN20 x DN15 RA454 DN20 x DN15 x DN15 F417 DN25 (25mm OD) x DN25 (25mm OD) x DN20	No61 Stop End RA514 DN15 RA518 DN20	Slip Coupling RA3008 DN15 RA3016 DN20 RA3020 DN25	Flared Compression Adaptor RA610 DN15 x DN15 Flare RA612 DN20 x DN20 Flare	SharkBite Tail x OD Reducer RA720 DN15 x DN20 Tail RA722 DN15 x DN25 Tail RA724 DN20 x DN25 Tail	Ball Valves BVRA670 DN15 x DN15 BVRA672 DN20 x DN20 BVRA680 DN15 x 15mm Fl BVRA682 DN20 x 20mm Fl BVRA682M DN20 x 20mm ML	

CONVERSION FITTINGS - COPPER

			
F009 Coupling DN15 Cu to 16mm OD	F017 Coupling DN20 Cu to 20mm OD	F363 16mm SharkBite to 15mm Copper Center Tee	F371 20mm SharkBite to 20mm Copper Center Tee
SharkBite to Copper 15-20mm		For use on SharkBite with Copper Take-off	Copper must comply to AS 1432
			
F250 Elbow 16mm SharkBite to 15mm Copper	F258 Elbow 20mm SharkBite to 20mm Copper	F364 15mm Copper to 16mm SharkBite Center Tee	F372 20mm Copper to 20mm SharkBite Center Tee
SharkBite to Copper 15-20mm		For use on Copper with SharkBite Take-off	Copper must comply to AS 1432

CONVERSION FITTINGS - PEX

			
F009PX Coupling 16mm	F017PX Coupling 20mm	F364PX Tee 16mm	F372PX Tee 20mm
SharkBite to PN20 PEX		For use on PN20 with SharkBite Take-off	Push-To-Connect plumbing solution from PN20 to SharkBite. Eg. Rehau PexPlus, Iplex K2, Forzapex, Tradepex & others.
			
F009PB Coupling 16mm OD to 18mm PB	F017PB Coupling 20mm OD to 22mm PB	F364PB Tee 16mm OD to 18mm PB	F372PB Tee 20mm OD to 22mm PB
SharkBite to Polybutylene		For use on Polybutylene with SharkBite Take-off	Push-To-Connect plumbing solution from Polybutylene to SharkBite. Eg. Iplex ProFit, Buteline, Hep 20, & others.
			
F009AP Coupling PN16 16mm	F017AP Coupling PN16 20mm	SharkBite to PN16, Aupsex & others	
		PEX Conversion Fittings are NOT suitable for connection on aluminium multi-layer PEX Systems	



PIPE

					
Potable Water (Mustard) F860 16mm OD 5m Straight F864 16mm OD 50m Coil F864100 16mm OD 100m Coil F870 20mm OD 5m Straight F874 20mm OD 50m Coil F874100 20mm OD 100m Coil F880 25mm OD 5m Straight F882 25mm OD 25m Coil	Hot Water (Red) F860R 16mm OD 5m Straight F864R 16mm OD 50m Coil F870R 20mm OD 5m Straight F874R 20mm OD 50m Coil F880R 25mm OD 5m Straight F882R 25mm OD 25m Coil	Recycled Water (Lilac) F862L 16mm OD 25m Coil F870L 20mm OD 5m Straight F872L 20mm OD 25m Coil F882L 25mm OD 25m Coil	Rain Water (Green) F860G 16mm OD 5m Straight F862G 16mm OD 25m Coil F870G 20mm OD 5m Straight F872G 20mm OD 25m Coil F880G 25mm OD 5m Straight F882G 25mm OD 25m Coil	Pipe in Conduit (Mustard only) F863 16mm OD 25m Coil F873 20mm OD 25m Coil	Foam Pipe Insulation (Red only) F862RR3 25m x 16mm pre-insulated PEX R0.3 F872RR3 25m x 20mm pre-insulated PEX R0.3 F882RR3 25m x 25mm pre-insulated PEX R0.3 F862RR8 25m x 16mm pre-insulated PEX R0.8 F872RR8 25m x 20mm pre-insulated PEX R0.8 F882RR8 25m x 25mm pre-insulated PEX R0.8
					
Corrugated Sleeve - Conduit Only F706 23mm ID Black to suit 16mm OD & 20mm OD 25m Coil F707 29mm ID Black to suit 25mm OD 25m Coil					






PIPE PROTECTION & SUPPORT

	Tube Clips F820 16mm OD Timber Nail F830 20mm OD Timber Nail F850 25mm OD Timber Nail F822 16mm OD Masonry Nail F832 20mm OD Masonry Nail F852 25mm OD Masonry Nail F824 16mm OD Tek Screw F834 20mm OD Tek Screw F854 25mm OD Tek Screw F826 16mm OD Concrete Anchor F836 20mm OD Concrete Anchor F828 16mm OD Metal Stud F838 20mm OD Metal Stud
	Chasing Sleeve F704 200m Flat Coil Note: To suit 16mm, 20mm & 25mm SB
	Silicone Wrap (self-adhesive) F708 50mm x 3m
	Tube Bend Support F840 16mm F842 20mm F844 25mm

TEMPERING VALVES

	Insulated Tempering Valves with SharkBite® PEX Fittings MIXF11009I 16mm PEX Insulated Standard MIXF11012I 20mm PEX Insulated Standard MIXF11116I 16mm PEX Insulated Ultra Solar MIXF11117I 20mm PEX Insulated Ultra Solar		4 in 1 Tempering Valves - DOWN MIX11014D Mix 16mm SB MIX11013D Mix 20mm SB
	Insulated Tempering Valves with SharkBite® Copper Fittings MIXRA11009I 15mm Cu Insulated Standard MIXRA11116I 15mm Cu Insulated Ultra Solar		4 in 1 Tempering Valves - UP MIX11014U Mix 16mm SB MIX11013U Mix 20mm SB

TOOLS & ACCESSORIES

	Pipe De-Coiler UFH034 Pipe De-Coiler Note: For use with 16mm & 20mm, 50m & 100m coils		Tube Cutter F700 16mm OD to 25mm OD (Ratchet) F701 16mm OD to 25mm OD		Disassembly Tongs F711 16mm OD Yellow (PEX) F713 20mm OD Green (PEX) F715 25mm OD Chrome (PEX) RA711 DN15 Red (Cu) RA713 DN20 White (Cu)		Disassembly Clips F710 16mm OD F712 20mm OD and DN20Cu RA710 DN15Cu		Copper Deburrer & Depth Gauge F702 DN15, DN20, DN25
-------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------	------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------	-------------------------------------------------------------------

STARTER PACK

	Starter Pack F4001 Starter Pack (fittings sold separately)
---------------------------------------------------------------------------------------	----------------------------------------------------------------------