

Multipurpose Expanding Foam Filler Polyurethane Foam



DESCRIPTION:

Multipurpose Expanding Foam Filler is an easy to install and will expand to fill gaps of all dimensions and in the most difficult locations. It will greatly reduce noise, draughts and dust & will block access by rodents. Foam Filler is a great insulator against heat or cold. The foam also has powerful adhesive properties, bonding well to timber, brick, concrete, galvanised steel, aluminium glass, fibre cement-sheet and plasterboard. Foam Fillers will not shrink and cures to an airtight, moisture resilient seal. Cured foam can be cut, sanded and painted to a neat finish.

FEATURES & BENEFITS:

- Expands 45 times
- Touch Dry in 30 Minutes.
- Dries in 8 hours.
- Ozone Friendly

APPLICATION DIRECTIONS:

- Surfaces must be clean and sound, free of dust, oil and grease. Make sure the surface temperature is above 5°C.
- Moisten substrate before application and cover surrounding surface to prevent contact with foam.
- **Shake the can well 15-20** times to mix contents. Screw in the application tube with trigger onto the can. Invert the can and direct the tube into the cavity and activate foam flow by applying pressure to the trigger.
- Large cavities should be filled in stages moistening with a mist spray between layers to maximise yield. Fill about one third of the space and allow time for expansion of the foam. The foam will skin after 15-30 minutes. Apply a water mist into the cavity and onto the foam to accelerate expansion. Install the next layer of foam and repeat until the cavity is almost filled. Allow some room for expansion.

CURING:

Maximum expansion takes about 12 hours but sanding, cutting or painting can be done after 8 hours.

YIELD/ COVERAGE:

Foam Filler will expand up to 45 minutes the can content.

PRECAUTIONS:

- Do not use in vehicle or foot traffic areas.
- Foam Filler is not suitable as a load bearing material.
- It should not be immersed in water.
- Cured foam will darken when exposed to sunlight.
- It can be protected by coating with an exterior grade acrylic paint when used in weather exposed applications.

CLEAN UP:

Uncured foam can be clean from non-porous surfaces by wiping with a cloth of moistened with solvent such as Foam Filler Cleaner. If Foam Filler is split on carpet or textiles, do not wipe off. Allow to fully cure before removing mechanically.

FIRST AID MEASURES:

IF ON SKIN: Wash with plenty of water and soap

IF INHALE: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get Medical advice/ attention. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Dispose of container as hazardous waste.

WARRANTY STATEMENT:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification. We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with the relevant Australian Standard and the Manufacturer's instructions, Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control. Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

PHONE: 1800 242 931
EMAIL: info@rlapolymers.com.au

MAIL: 215 Colchester Road Kilsyth Victoria 3137
(Attention Customer Service)
WEBSITE: www.rlapolymers.com.au

AUSTRALIAN CONSUMER LAW:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

DISCLAIMER:

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Version 1

Issue date:12/07/2022

RLA Polymers Pty Ltd ACN 004 709 915

Head Office
215 Colchester Road
Kilsyth, Victoria, 3137
Tel: 1800 242 931

New South Wales
363 Wentworth Ave
Pendle Hill, N.S.W, 2145

Queensland
57 Fulcrum Street
Richlands, QLD, 4077

South Australia
Unit 2/7 Berger Road
Wingfield ,SA, 5013

Western Australia
24 Hanwell Way
Bassendean, W.A, 6054
Tel: 08 9279 8911

For the latest product information please visit rlapolymers.com.au